

# Task Master™ - Titan 435A



- Adjustable water drain operators seat.
- Padded steering wheel and shock seat suspension for comfortable operation.
- Accepts all standard category one 3-point implements.
- Hydraulic power steering provides for easy turning even with a full loader bucket.
- Standard 6 spine 1 3/8" Power Take Off (PTO) shaft with standard 540 RPM speed operates all standard PTO powered implements.
- Live hydraulic system provides full time power to 3-point implements, power steering, loader, etc. even when clutch is depressed.
- Foldable ROPS (Roll Over Protective Structure) for going under trees or in garage.
- Foot and hand throttle control for easy operation.
- Two-stage clutch allows you to stop the tractor and/or change gears and keeps a PTO operated implement under full power.
- Driver Selectable 2 or 4 wheel drive.
- Sun Shade included free

## FEATURES

### Engine

- > Fast Start Direct Injection
- > Three Cylinder Diesel
- > Liquid Cooled Engine
- > Foot & Hand Engine Throttle
- > Dry Paper Air Filter

### Instrumentation

- > Hour Meter
- > Rocker Switches
- > Engine Oil Pressure Gauge
- > Alternator Amp Meter
- > Engine Speed Gauge

### Power Train

- > Selectable 4 Wheel Drive
- > Dual Stage Clutch
- > Foot Operated Differential Lock
- > Two Speed Live Power Take Off
- > Adjustable Offset Rear Wheels

### Lights & Electrical

- > 12-Volt System
- > Heavy Duty Starter
- > Front Headlights
- > Hazard / Signal Lights
- > Brake and Running Lights
- > Dual Rear Work Lights

### Tractor Hitches

- > EZ Stor Swing Type Draw Bar
- > Sway links for Hitch Arms
- > Leveling Lift Links
- > Crank Type Leveling Arm

### Safety Equipment

- > Rear Wheel Brakes
- > Parking Brake
- > Safety Start Clutch Switch
- > Roll Over Protective Structure
- > Seat Belts
- > PTO Shield
- > Auto Lock fuel shutoff

### Tractor Hydraulics

- > Full Power Steering
- > Live Hydraulic Power
- > Hitch Lowering Speed Control
- > Two Hydraulic Pumps

### Other Equipment

- > Rear Wheel Weights

## SPECIFICATIONS

Engine	Gross 35 Hp
PTO Hp (dynameter)	33 Hp*
Engine	395 / 2.2 liter
Bore & Stroke (mm)	95 x 105
Engine Displacement	136 cu.in.
Engine speed	2400 rpm
Fuel Capacity	8 gal.
Battery Cold Cranking	575 amps
Transmission (4+1x2)	8 forward 2 reverse
Clutch	Dual Stage
PTO (Live)	1 3/8" 6-spline
PTO Speed	540 & 1000 rpm
PTO Clutch	Dry Disc
3-point Hitch	ASAE Cat. 1
Lift Capacity	1350 #
Hydraulic Pumps	10 ml /r~6.3gpm @ 2200 rpm 16 ml /r~9.6gpm
Wheel Base	67"
Wheel Tread	44"~52"
Turning Radius	110"
Overall Length	133"
Overall Width (minimum)	58"
Ground Clearance	14"
Height ROPS	91"
Height Steering Wheel	61"
Tractor Weight	3509 lbs
Front Tire Size	7.5 x 16
Rear Tire Size	12.4 x 24
Speed Range	0.93-21.3 mph



Features and specifications are subject to change or corrections without notice and without incurring obligation on behalf of Mazama Products or the Seller. \*PTO HP values are estimated. Loaders and implements are extra!  
06/05

**NOTICE!** The Seller is solely responsible for the proper and safe operation of the tractor at time of delivery and for all client support after the sale. The Seller provides warranty labor and the manufacturer warrants parts for 12 months to the original purchaser. Task Master Equipment, Llc, makes no expressed or implied warranty of any kind and is not responsible for actions of seller. Questions or Comments: 1-541-895-2959 or Email [taskmaster@centurytel.net](mailto:taskmaster@centurytel.net).