


# Engineering Laboratories, Inc.

Over Fifteen Years Serving The Industry Worldwide

Phone: 670-506-0000  
www.vandeenburghengr.com  
info@vandeenburghengr.com




## BV-300 Series Reclaimer



Just Right For Industrial Use

## JV-90 Series Reclaimer



Ideal For In-Shop Work

## LV-30 Series Reclaimer



Perfect For Facility Maintenance & Manufacturing

## CV-15 Series Reclaimer



Designed For Extreme Mobility

## RV-10 Series Recovery Unit



Unbeatable For Rapid & Numerous Changing of Refrigerants

## VS-29 Series Deep Vacuum



Great For Pulling To Deep Vacuum Levels

### Dimensions

Width 42 in. / 106.7 cm  
Depth 24 in. / 61.0 cm  
Height 60 in. / 152.4 cm

### Weight

Approximate 725 lbs. / 329 kg

### Compressor

2 Horsepower

Hermetic

### Electrical

208/230, 60Hz, 1Ph

### Amperage

20 amp service

### Reclaim Capacity

Liquid 5 lbs. / 2.3 kg Per Minute

### On-board Storage

300 lbs. / 136 kg

### Valves

1/4 in. / 6.3 mm SAE (3/8 in. Available)  
Steel Powder Coat

### Cabinet

28 in. / 71.1 cm  
24 in. / 61.0 cm  
60 in. / 152.4 cm

460 lbs. / 209 kg

2 Horsepower

208/230, 60Hz, 1Ph

20-amp service

5 lbs. / 2.3 kg Per Minute

90 lbs. / 41 kg

1/4 in. / 6.3 mm SAE (3/8 in. Available)  
Steel Powder Coat

24 in. / 61.0 cm  
18 in. / 45.7 cm  
41 in. / 104.1 cm

250 lbs. / 113 kg

1 Horsepower

115/120, 60Hz, 1Ph

15-amp service

3 lbs. / 1.4 kg Per Minute

30 lbs. / 14 kg

1/4 in. / 6.3 mm SAE  
Steel Powder Coat

28 in. / 71.1 cm  
24 in. / 61.0 cm  
45 in. / 114.3 cm

223 lbs. / 101 kg

1 Horsepower

115/120, 60Hz, 1Ph

15-amp service

3 lbs. / 1.4 kg Per Minute

15 lbs. / 7 kg

1/4 in. / 6.3 mm SAE  
Steel Powder Coat

20 in. / 50.8 cm  
23.5 in. / 59.7 cm  
33 in. / 83.8 cm

121 lbs. / 54.5 kg

1/2 Horsepower

115/120, 60Hz, 1Ph

10-amp service

1.2 lbs. / .5 kg Per Minute

None

1/4 in. / 6.3 mm SAE  
Steel Powder Coat

20 in. / 50.8 cm  
23.5 in. / 59.7 cm  
33 in. / 83.8 cm

90 lbs. / 40.8 kg

1 Horsepower

115/120, 60 Hz, 1Ph

10-amp service

Not Applicable

None

1/4 in. / 6.3 mm SAE  
Steel Powder Coat

## Refrigerants (not all machines can handle all refrigerants)

R-12, R-22, R-134a, R-401A, R-401B, R-401C, R-402A, R-402B, R-404A, R-406A, R-407C, R-407D, R-408A, R-409A, R-410A, R-410B, R-411A, R-411B, R-412A, R-414A, R-414B, R-416A, R-500, R-502, R-509 ... and more

## Additional Available Equipment:

Safe Safe Storage Systems (Optional)

## Users Include:

Airtrak, Carrier Corporation, Doeing, Copeland Hong Kong, Copeland USA, Chrysler Motors, Kroger Company, Hyatt Regency, Lockheed Martin, New York Transit Authority, Rocky Mountain Reclamation Center, San Diego Trolley, Inc., Saudi Petrochemical, Trane Corporation, Thermo King Corporation, U.S. Department Of Defense, United Air Lines, Winn Dine Stores ... and many, many, more

## Features Include:

- Alternate & International Voltages Available
- Designed for Years of Dependable Service
- Exclusive Patented Liquid Injection
- Manufactured to customer's specifications with options to handle R-12, R-22, R-500 & R-502 and all alternates in the same range with one machine utilizing a unique multiple thermal expansion valve design
- Measurable Oil Out Of Equipment Being Serviced
- Meets All EPA Certification Requirements