

Rev; July 31, 2009

Specifications

Length	5.43 m / 17' 8"
Beam	2.39 m / 94"
Height of Sides	84 cm / 33"
Bottom Width	1.83 m / 72"
Approx. Dry Weight	1035 kg / 2281 lbs
Deadrise	8 degrees
Fuel Capacity	135 L / 36 USG
Heavy duty hull specifications;	
Bow section	6.4 mm / 0.25
Wings 6061	6.4 mm / 0.25
Center keel 6061	9.5 mm / 0.375
Transom Reinforcing	6.4 mm / 0.25
Under floor 6061 extruded stringers	9



Boat may not be exactly as shown

Standard Features**Hull Features**

Parabolic tapered hull
 Pre-Flex® hull technology
 Full length performance delta keel
 Engineered reverse chines
 9 under floor 6061 extruded stringers
 UHMW Bottom protection
 1/2" main section
 1" Total keel thickness
 Single piece hull sides with wide formed gunnels
 Anchor rope locker
 (3) 8" welded bow and stern cleats
 Stainless steel bow and stern eyes
 Welded 5 piece windshield with tempered glass windows
 Heavy duty chine extrusions
 Extreme heavy duty EZ clean intake grate
 Binnacle mount throttle and shift
 Welded grab rails on windshield
 Full width heavy duty reinforced swim platform
 Starboard side steering
 Welded aluminum glove box compartment with lock
 Unpainted sides and hull interior

Electric Features

Gauge package includes; tach and volt
 Navigation light package
 Battery holder and electric horn
 (2) Electric 1100 gpm bilge pumps and (1) bilge blower

Interior Features

2 Swivel Fishmaster seats with pinchless hinges on pedestals
 270 degree jet helm and steering wheel
 Marine vinyl floor
 2 cup holders
 Self bailing drop bow

Power

Mercury 200 hp Optimax Sport Jet, complete with stainless steel impeller

Trailer / Standard with Boat Package

EZ Loader 2800 lb factory matched galvanized single axle bunk trailer with custom tie down straps

