

Rev; November 10, 2009

**Specifications**

Length	6.12 m / 20' 1"
Beam	1.93 m / 76"
Height of Sides (Tapered)	61 cm / 24"
Bottom Width	1.68 m / 66"
Approx. Dry Weight	998 kg / 2200 lbs
Deadrise	Constant 16 degrees
Fuel Capacity	159 L / 42 USG

**Aluminum Thickness**

Side	3.2 mm / 0.125"
Bottom	4.83 mm / 0.190"
Transom Thickness	4.83 mm / .190"
Bottom Alloy	5086
Keel Plate around intake	12.7 mm / .5"



Boat may not be exactly as shown

**Standard Features****Hull Features**

Pre-Flex® hull technology  
 Full length performance delta keel  
 Engineered full length reverse chines  
 Performance lifting strakes  
 Formed compound angle box stringers / full length  
 4" Drop bow with color match armor deck  
 Single piece hull sides with formed gunnels  
 Welded 5 piece windshield with tempered glass windows  
 Stainless steel bow and stern eyes  
 Welded aluminum glove box compartment with lock  
 Integrated swim platform  
 Heavy duty QT100 EZ clean intake grate  
 Painted gunnels, windshield and hull sides  
 Painted gunwhales, walk-thru windshield  
 Color matched side decals and pin stripping

**Electric Features**

Gauge package includes; fuel, tach, volt,  
 oil pressure and water temperature gauges  
 12V power point  
 Navigation lights package with stern light  
 Battery holder & electric horn  
 Bilge pump, bilge blower  
 Main wiring harness with water tight connections & labeled wires

**Interior Features**

Port side helm  
 Hot foot throttle control  
 Side mount reverse lever  
 Full width rear bench seat  
 Motor box storage  
 Bow dry storage (14 cu ft)  
 2 Sportmaster bucket seats with sliders - floor mounted  
 Marine Vinyl floor  
 Lavezzi sport steering wheel with tilt  
 4 cup holders  
 Stainless steel passenger grab rail

**Power**

5.7 L 320 hp V8 Port Fuel Injection Engine with  
 American Turbine pump with SD - 309

**Trailer / Standard w/ Boat Package**

EZ Loader 2800 lb factory matched galvanized single axle  
 bunk trailer w/ custom tie down straps