

Rev; July 31, 2009

Specifications

Length	6.3 m / 20' 8"
Beam	2.24 m / 88"
Height of Sides	91 cm / 36"
Bottom Width	1.8 m / 72"
Approx. Dry Weight	820 kg / 1810 lbs
Deadrise	Constant 12 degrees
Fuel Capacity	Optional
Maximum HP	150 hp
Transom height	51 cm / 20"
Aluminum Thickness	
Sides	3.2 mm / 0.125
Bottom	4.8 mm / 0.19



Boat may not be exactly as shown

Standard Features**Hull Features**

Pre-Flex® hull technology
 Full length performance delta keel
 Engineered full length reverse chines
 Performance lifting strakes
 Formed compound angle box stringers / full length
 Welded bow stem / heavy duty keel guard
 Single piece hull sides with wide formed gunnels
 Hinging front drop ramp weather tight enclosure with stainless steel locking clamps
 4 welded bow and stern cleats
 Stainless steel bow and stern eyes
 Self bailing deck with 2 - high-flow 3 1/4" freeing ports
 Marine grade pressure treated plywood with marine vinyl covering
 Unpainted sides and hull interior

Electric Features

12V power point
 Navigation lights package
 Battery holder and electric horn
 Electric 1100 gph bilge pump

Available Option Packages**Center Console Package**

(Specify mounting location of console)
 Welded aluminum center console with storage shelf
 Sport helm and steering wheel
 Transom-mount 24" leaning pad seat
 Storage compartment
 Fold-down aluminum / glass windshield

Dual Console Package

(Specify mounting location of consoles)
 Welded aluminum consoles with storage area
 Welded 3 piece windshield with tempered glass windows
 Sport helm and steering wheel
 2 Swivel Fishmaster seats with pinchless hinges on pedestals
 Walk thru welded windshield and canvas weather guard

