

Rev; July 31, 2009

Specifications

Length	6.3 m / 20' 8"
Beam	2.36 m / 93"
Height of Sides	79 cm / 31"
Bottom Width	1.83 m / 72"
Approx. Dry Weight	1000 kg / 2200 lbs
Deadrise	Constant 8 degrees
Fuel Capacity	170 L / 45 USG
Aluminum Thickness	
Side	3.2 mm / 0.125
Bottom	4.8 mm / 0.19
Hull Alloy	5086



Boat may not be exactly as shown

Standard Features**Hull Features**

Pre-Flex® hull technology
 Full length performance delta keel
 Engineered reverse chines
 Performance lifting strakes
 Formed compound angle box stringers / full length
 Welded bow stem / heavy duty keel guard
 Single piece hull sides with wide formed gunnels
 Closed cell polyurethane foam below deck
 Forward anchor rope storage
 Stainless steel bow and stern eyes
 Bow deck platform with storage
 Pump guard and swim platform
 Race inspired performance tunnel
 (4) 8" welded cleats
 Unpainted sides and hull interior

Electric Features

Gauge package includes; fuel, tach, volt
 12V power point
 Navigation lights package
 Battery holder and electric horn
 Electric 1100 gph bilge pump and bilge blower

Interior Features

Leaning pad seat
 Center console with 270 degree jet helm and steering wheel
 Fold-down aluminum / glass windshield
 Single lever binnacle throttle and shift control
 Side storage trays
 Marine vinyl floor
 Console mounted cup holder
 Bow casting deck with storage
 Forward anchor rope storage

Power

Mercury 200 hp Optimax Sport Jet, complete with stainless steel impeller

Trailer / Standard with Boat Package

EZ Loader 2800 lb factory matched galvanized single axle bunk trailer with custom tie down straps

Kodiak Package

ATV ramps
 ATV tie downs
 Transom wheel kit
 Camo 1/2 top includes side windows with gun ports and drop curtain

