



AEOLUS

AEOLUS HN267

PREMIUM STEER

An all-position premium line-haul steer tire that provides solid wear and durability. In addition to line-haul service, this tire performs well in regional steer applications. The HN267 features a decoupling groove which is optimal for steer position applications.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
704367	11R22.5	14	143/139	M	41.5	11.0	19	8.25	19.4	502	129	6175@105	5840@105
704369	11R22.5	16	146/143	M	41.5	11.0	19	8.25	19.4	502	131	6610@122	6005@120
704445	11R24.5	14	145/141	M	43.5	11.0	19	8.25	20.3	480	134	6610@105	6005@105
704446	11R24.5	16	148/144	M	43.5	11.0	19	8.25	20.3	480	136	7160@120	6610@120
704378	295/75R22.5	14	144/141	M	39.9	11.7	19	8.25	18.7	522	126	6170@107	5670@102
704448	285/75R24.5	14	144/141	M	41.3	11.1	19	9.00	19.3	504	130	6170@107	5670@102

AEOLUS HN257

PREMIUM RIB

An all-position radial truck tire optimized for steer axles. This tire is ideally suited for regional applications and limited highway service.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
722366	11R22.5	14	143/139	M	41.5	11.0	19	8.25	19.4	502	124	6175@105	5840@105
722369	11R22.5	16	146/143	M	41.5	11.0	19	8.25	19.4	502	125	6610@120	6005@120
722445	11R24.5	14	145/141	M	43.5	11.0	19	8.25	20.3	480	134	6610@105	6005@105
722446	11R24.5	16	148/144	M	43.5	11.0	19	8.25	20.3	480	137	7160@120	6610@120
722370	12R22.5	16	149/145	M	42.7	11.8	21	9.00	20.0	488	136	7390@122	6780@112
722375	255/70R22.5	16	140/137	M	36.6	10.0	16	7.50	17.1	569	100	5510@120	5070@120
722377	275/70R22.5	16	144/141	M	37.7	10.9	19	8.25	17.6	552	113	6940@130	6395@130
722379	315/80R22.5	18	154/151	M	42.4	12.3	21	9.00	19.8	492	152	8270@120	7610@120
722380	315/80R22.5	20	157/154	M	42.4	12.3	21	9.00	19.8	492	156	9090@130	8270@130



AEOLUS

AEOLUS HN06

ALL POSITION STEER / TRAILER

General all-purpose tire that is ideal for local delivery applications. Solid shoulders support even wear and resist curbing abuse.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
703317	9.00R20	14	141/136	L	40.1	10.2	18	7.00	18.7	520	111	5670@117	4970@107
703327	10.00R20	16	146/143	L	41.5	10.9	19	7.50	19.4	502	124	6610@122	5800@112
703367	11R22.5	14	143/139	M	41.5	11.0	19	8.25	19.4	502	129	6175@105	5840@105
703369	11R22.5	16	146/143	M	41.5	11.0	19	8.25	19.4	502	131	6610@122	6005@120
703378	295/75R22.5	14	144/141	M	39.9	11.7	19	8.25	18.7	522	126	6170@107	5670@102
703448	285/75R24.5	14	144/141	M	41.3	11.1	19	8.25	19.3	504	130	6170@107	5670@102

AEOLUS HN235

REGIONAL ALL POSITION

The combination of good traction and wear, together with a wide tread makes this a solid choice for line-haul and regional drive applications. This tire features a strong casing design for enhanced durability.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
718280	215/75R17.5	16	127/124	L	30.2	8.3	16	6.00	14.1	690	56	3860@120	3525@120
718282	235/75R17.5	18	143/141	J	31.4	9.2	16	6.75	14.7	663	-	6007@130	5677@130



AEOLUS

AEOLUS HN230+ ALL POSITION RIB

The HN230+ features a five rib pattern for even load distribution in any axle position. The wide grooves efficiently channel out water for superior wet traction.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
718680	8.25R15	18	143/141	G	33.3	9.3	16	6.50	15.3	635	72	6007@123	5677@123
718679	10.00R15	18	148/145	G	36.5	10.9	17	7.50	16.7	580	93	6944@123	6393@123
717375	255/70R22.5	16	140/137	M	36.6	10.1	18	7.50	17.1	565	97	5511@120	5070@120

AEOLUS HN828+ PREMIUM REGIONAL RIB

The wide tread design and solid shoulders of the HN828+ enhances driving stability and handling.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
702299	225/70R19.5	14	128/126	M	31.9	8.9	16	6.75	15.0	650	70	3968@110	3748@110
703302	245/70R19.5	16	135/133	M	33.1	9.8	17	6.75	15.4	625	78	4806@120	4542@120



AEOLUS

AEOLUS HN08

ON/OFF ROAD MIXED SERVICE ALL POSITION

An All Position Rib suitable for both on and off road applications. The HN08 provides excellent tread wear and is recognized for its cut and chip resistance. This tire features a four-rib design, deep tread depths and an aggressive shoulder for improved traction.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
706318	9.00R20	16	144/142	K	40.1	10.2	20	7.00	19	520	114	6170@130	5840@130
706327	10.00R20	16	146/143	K	41.5	10.9	21	7.50	19	502	128	6610@122	5800@112
706332	11.00R20	16	149/145	K	42.7	11.5	21	8.00	20	488	144	7200@122	6320@112
706340	12.00R20	18	154/149	K	44.3	12.4	22	8.50	21	471	168	8210@122	7200@122
706404	12.00R24	18	158/153	K	48.2	12.4	22	8.50	23	432	173	9240@122	8105@122
706369	11R22.5	16	146/143	L	41.5	11.0	21	8.25	19	502	133	6610@122	6005@120
706446	11R24.5	16	148/144	L	43.5	11.0	21	8.25	20	480	135	7160@120	6610@120
707370	12R22.5	16	149/145	L	42.7	11.8	21	9.00	20	488	145	7390@122	6780@112
706447	12R24.5	16	152/149	L	44.7	11.8	21	9.00	21	466	151	7826@120	7165@120
706380	315/80R22.5	20	157/154	L	42.4	12.3	21	9.00	20	492	155	9090@130	8270@130

AEOLUS HN808

PREMIUM LINE HAUL TRAILER

The shallow non-skid tread resists developing irregular wear in free rolling wheel positions and minimizes skid wear. Excellent traction is achieved on both wet and dry surfaces by channeling water through the lateral grooves and the large center groove to provide a consistent footprint on the road surface.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
700367	11R22.5	14	143/139	M	41.5	11.0	13	8.25	19.4	502	123	6175@105	5840@105
700445	11R24.5	14	145/141	M	43.5	11.0	13	8.25	20.3	480	129	6630@105	6005@105
700378	285/75R24.5	14	144/141	M	41.3	11.1	14	8.25	19.3	506	130	6170@107	5670@102
700448	295/75R22.5	14	144/141	M	39.9	11.7	14	9.00	18.7	522	126	6170@107	5670@102



AEOLUS

AEOLUS HN826+ PREMIUM RIB

The HN826+ features an application specific shoulder design for enhanced handling and resistance to irregular wear in high scrub areas.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
701279	215/75R17.5	16	127/124	L	30.2	8.3	16	6.00	14.1	690	56	3860@120	3525@120
701282	235/75R17.5	18	143/141	J	31.4	9.2	16	6.75	14.7	663	-	6007@130	5677@130

AEOLUS HN308+ PREMIUM CLOSED SHOULDER DRIVE

A premium line haul drive tire that features a solid shoulder, which provides superior stability and resistance to irregular wear.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
710367	11R22.5	14	143/139	K	41.9	11.0	26	8.25	20	497	133	6175@105	5840@105
710369	11R22.5	16	146/143	K	41.9	11.0	26	8.25	20	497	136	6610@120	6005@120
710445	11R24.5	14	145/141	K	43.5	11.0	26	8.25	20	480	144	6610@105	6005@120
710446	11R24.5	16	148/144	K	43.5	11.0	26	8.25	20	480	146	7160@120	6610@120
710378	295/75R22.5	14	144/141	M	40.2	11.7	26	8.25	19	519	130	6170@107	5670@102
710448	285/75R24.5	14	144/141	M	41.6	11.1	26	9.00	19	502	133	6170@107	5670@102



AEOLUS

AEOLUS HN306

PREMIUM OPEN SHOULDER DRIVE

The combination of good traction and wear, together with a wide tread makes this a solid choice for line-haul and regional drive applications. This tire features a strong casing design for enhanced durability.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
709367	11R22.5	14	143/139	M	41.9	11.0	26	8.25	20	497	137	6175@105	6840@105
709369	11R22.5	16	146/143	M	41.9	11.0	26	8.25	20	497	139	6610@120	6005@120
710445	11R24.5	14	145/141	M	43.5	11.0	26	8.25	20	480	151	6430@107	5640@97
709446	11R24.5	16	148/144	M	43.5	11.0	26	8.25	20	480	153	7160@120	6610@120
709370	12R22.5	16	149/145	M	42.7	11.8	26	9.00	20	488	150	7390@122	6780@112
709378	285/75R24.5	14	144/141	M	41.6	11.1	26	8.25	19	502	137	6170@107	5670@102
709448	295/75R22.5	14	144/141	M	40.2	11.7	26	9.00	19	519	134	6170@107	5670@102

AEOLUS HN357

REGIONAL DRIVE

An ideal mixed-service tire, the HN357's staggered tread block design distributes forces evenly to resist irregular wear and provides superior traction in rain, mud and snow.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
711369	11R22.5	16	146/143	M	41.5	11.0	26	8.25	19	502	129	6610@122	6005@120
711446	11R24.5	16	148/144	M	43.5	11.0	26	8.25	20	480	139	7160@120	6610@120



AEOLUS

AEOLUS HN353

ON/OFF ROAD DRIVE

The HN353 is an aggressive radial truck tire designed for on/off road service in severe conditions. Its rugged directional tread provides outstanding self-cleaning capabilities and its deep lateral shoulder grooves aid water dispersion to enhance traction. The outer rows of tread blocks on the new HN356 have been fitted with sipes to further improve wet traction.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
723369	11R22.5	16	146/143	M	41.5	11.0	28	8.25	19	502	143	6610@122	6005@120
723446	11R24.5	16	148/144	M	43.5	11.0	28	8.25	20	480	147	7160@120	6610@120
723370	12R22.5	16	149/145	M	42.7	11.8	25	9.00	20	488	148	7390@122	6780@112
723371	13R22.5	18	154/151	M	44.3	12.6	26	9.75	21	471	166	8270@120	7610@120
723379	315/80R22.5	18	154/151	M	42.4	12.3	25	9.00	20	492	154	8270@120	7610@120
723380	315/80R22.5	20	157/154	M	42.4	12.3	25	9.00	20	492	159	9090@130	8270@130

AEOLUS HN266

ON/OFF ROAD ALL POSITION

The HN266 is engineered for use in both on and off road applications. The tread design of the HN266 features a deep 23/32" tread depth to deliver superior tread wear and excellent traction required for many applications.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
733369	11R22.5	16	148/144	L	41.7	10.9	23	8.25	19	501	131	6614@120	6007@120
733446	11R24.5	16	149/146	L	43.3	11.3	23	8.25	20	482	132	7165@120	6614@120
733380	315/80R22.5	20	157/154	L	42.7	12.4	23	9.00	20	492	157	9094@130	8267@130



AEOLUS

AEOLUS HN355

PREMIUM REGIONAL DRIVE

An all weather premium drive tire optimized for exceptional traction and mileage. This tire's wide footprint and square shoulders provide enhanced stability and control.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
715369	11R22.5	16	146/143	M	41.5	11.0	28	8.25	19	502	135	6610@122	5800@112
715446	11R24.5	16	148/144	M	43.5	11.0	28	8.25	20	480	147	7035@122	6170@112
715375	255/70R22.5	16	140/137	M	36.6	10.0	25	7.50	17	569	111	5510@120	5070@120
715377	275/70R22.5	16	144/141	M	37.7	10.9	25	8.25	18	551	124	6175@120	5675@120
715379	315/80R22.5	18	154/151	M	42.4	12.3	29	9.00	20	492	162	8270@120	7610@120
715380	315/80R22.5	20	157/154	M	42.4	12.3	29	9.00	20	492	166	9090@130	8270@130

AEOLUS HN596

ON/OFF ROAD DRIVE

The HN596's tread features an extra deep block pattern designed to provide superior handling in both on and off road applications. This tire has won favor in demanding applications such as logging and construction sites.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
712369	11R22.5	16	146/143	M	42.2	11.0	26	8.25	20	494	145	6610@122	5800@112
712446	11R24.5	16	148/144	M	44.2	11.0	26	8.25	21	471	147	7035@122	6170@112



AEOLUS

AEOLUS HN324

MIXED SERVICE DRIVE

The deep wide tread block provides superior wear resistance. The tread pattern has been proven to offer reduced road noise.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
713370	12R22.5	16	149/145	L	42.7	11.8	26	9.00	20	488	148	7390@122	6780@112
713447	12R24.5	16	152/149	L	44.7	11.8	26	9.00	21	466	155	7826@120	7165@120
713332	11.00R20	16	149/145	L	42.7	11.1	26	8.00	20	488	147	7200@122	6320@112

AEOLUS HN366

PREMIUM OPEN SHOULDER DRIVE

The tread design of the HN366 provides a good balance between traction and tread life across a wide range of applications.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
716299	225/70R19.5	14	128/126	M	31.9	8.9	16	6.75	15	650	73	3968@110	3745@110
716302	245/70R19.5	16	136/134	M	33.1	9.8	17	7.50	15	625	82	4806@120	4541@120



AEOLUS

AEOLUS HN228

ON/OFF ROAD MIXED SERVICE ALL POSITION

The HN228 is available in low profile sizes to provide a wide footprint on the road. This tire features an aggressive tread design giving the HN328 excellent traction. In its 385, 425 and 445 sizes, the HN328 is well suited for super single applications.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
708375	255/70R22.5	16	140/137	L	36.6	10.0	25	7.50	17	569	107	5510@120	5070@120
708377	275/70R22.5	16	144/141	L	37.7	10.9	25	8.25	18	552	119	6175@120	5675@120
708381	385/65R22.5	18	158	L	42.2	15.3	21	11.75	20	494	169	9370@120	-
708382	425/65R22.5	20	164	K	44.3	16.6	21	12.25	21	472	185	11022@120	-
708383	445/65R22.5	20	164	K	45.4	17.5	21	13.00	22	456	203	12345@120	-

AEOLUS HN207

ALL POSITION RIB

The all-position wide base HN207 is designed to deliver superior mileage and solid traction in mixed operations.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
707381	385/65R22.5	18	158	L	42.2	15.3	20	11.75	20	494	170	9370@120	-
707382	425/65R22.5	20	164	K	44.3	16.6	21	12.25	21	470	185	11022@120	-
707383	445/65R22.5	20	168	K	45.3	17.5	21	13.00	21	460	199	12345@120	-



AEOLUS

AEOLUS HN309

PREMIUM REGIONAL DRIVE

The tread design of the HN309 features wide lugs to provide exceptional traction on all road surfaces. The HN309 is an ideal all weather drive position tire.



Pr Code	Size	Ply Rating	L. I.	Speed Symbol	OD	SW	TD	RW	SLR	REVS/ MILE	WGT	LOAD	
												SINGLE	DUAL
731279	215/75R17.5	16	1.02	M	30.3	8.5	20	6.00	14	690	65	3858@120	3527@120