



IMPLEMENT TIRE (L-1)

Low cost high flotation farm wagon tires from American Farmer offer multi treads to protect against side slippage and enable the tires to grip in nay terrain and maintain directional stability



SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
14L16.1SL	D/8	FA3Z5	Dec-32	13.7	37	11	32	3860	52
14L16.1SL	F/12	FA3Z9	Dec-32	13.7	37	11	44	4680	58
16.5L16.1SL	D/8	FA335	15/32	16.6	40.5	14	28	4400	74
16.5L16.1SL	E/10	FA337	15/32	16.6	40.5	14	36	5200	83
16.5L16.1SL	G/14	FA33B	15/32	16.6	40.5	14	48	6400	89
16.5L16.1SL	H/16	FA33D	15/32	16.6	40.5	14	56	7003	102
19L16.1SL	E/10	FA347	16/32	19	42.4	16	32	6000	102
21.5L16.1SL	E/10	FA3AB	18/32	21.5	44.5	18	28	6600	111
21.5L16.1SL	G/14	FA3AC	18/32	21.5	44.5	18	36	7850	133

MAX SPEED 25 MPH - * MAX SPEED 55 MPH

IMPLEMENT(L-1) - TUBE TYPE

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
14L16.1SL	F/12	FA3ZA	Dec-32	13.7	37	11	44	4680	53

MAX SPEED 25 MPH

(HF-1) Tubeless Implement Tire

The HF-1 implement tire is a high flotation baler / implement tire with weight distribution across a huge footprint for less compaction and turf disturbance.



Implement (HF-1) Tubeless

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
25/7.50-15		TBA							
27/9.50-15		TBA							
31/13.50-15	D/8	FB3BN	Dec-32	13.5	32.4	13	45	2760	52



(I-1 Rib) Tubeless Implement Tire

These low cost, low profile tubeless high flotation farm wagon/ implement tires with broad load distribution offer the highest quality and durability.



IMPLEMENT(I-1 RIB) - TUBELESS									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
9.5L-14SL	D/8	FC1A5	Nov-32	9.7	29.6	7	44	2400	26
11L-14SL	D/8	FA3V5	Nov-32	10.5	30	8	36	2800	29
9.5L-15SL	C/6	FC1C3	Nov-32	9.7	30.5	7	32	2320	25
9.5L-15SL	D/8	FC1C5	Nov-32	9.7	30.5	7	44	2470	27
9.5L-15SL	F/12	FA3C9	Nov-32	9.7	30.5	7	64	3200	32
*9.5L-15FI	D/8	FA3DB	Sep-32	9.7	30.5	7	44	2670	32
11L-15SL	D/8	FC1D5	Oct-32	10.5	31.4	8	36	2540	30
11L-15SL	E/10	FC1D7	Oct-32	10.5	31.4	8	44	2910	34
11L-15SL	F/12	FC1D9	Oct-32	10.5	31.4	8	52	3200	37
*11L-15FI	D/8	FA3DC	Aug-32	10.5	31.4	8	60	3120	38
12.5L-15SL	D/8	FC1E5	Dec-32	12.2	33	10	36	3000	38
12.5L-15SL	E/10	FC1E7	Dec-32	12.2	33	10	44	3420	40
12.5L-15SL	F/12	FC1E9	Dec-32	12.2	33	10	52	3860	42
12.5L-15SL	H/16	FC1ED	Dec-32	12.2	33	10	60	4200	49
12.5L-15SL	L/20	FC1CT	Dec-32	12.2	33	10	68	4515	52
*12.5L-15FI	D/8	FA3DE	Nov-32	12.2	33	10	60	3740	48
*12.5L-15FI	F/12	FA3DF	Nov-32	12.2	33	10	90	4680	51
11L-16SL	D/8	FC1F5	Oct-32	10.2	31.4	8	36	2680	31
12.5L-16SL	F/12	FC1H9	Dec-32	11.4	33.4	10	52	3960	45
12.5L-16SL	G/14	FC1HB	Dec-32	11.4	33.4	10	56	4180	45

MAX SPEED 25 MPH - * MAX SPEED 55 MPH



IMPLEMENT(I-1 RIB) - TUBE TYPE									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
9.5L-14SL	D/8	FC1A6	Nov-32	9.7	29.6	7	44	2400	23
11L-14SL	C/6	FA3V4	Nov-32	10.5	30	8	28	2040	25
11L-14SL	D/8	FA3V6	Nov-32	10.5	30	8	36	2800	25
11L-14SL	E/10	FA3V8	Nov-32	10.5	30	8	44	3170	29
9.5L-15SL	D/8	FC1C6	Nov-32	9.7	30.5	7	44	2470	24
9.5L-15SL	E/10	FC1C8	Nov-32	9.7	30.5	7	52	3180	26
9.5L-15SL	F/12	FC1CA	Nov-32	9.7	30.5	7	56	3280	28
11L-15SL	D/8	FC1D6	Oct-32	10.5	31.4	8	36	2540	26
11L-15SL	F/12	FC1DA	Oct-32	10.5	31.4	8	52	3200	33
12.5L-15SL	D/8	FC1E6	Dec-32	12.2	33	10	36	3000	34
12.5L-15SL	E/10	FC1E8	Dec-32	12.2	33	10	44	3420	36
12.5L-15SL	G/14	FC1EC	Dec-32	12.2	33	10	56	4600	38
11L-16SL	D/8	FC1F6	Oct-32	10.2	31.4	8	36	2680	27
11L-16SL	F/12	FC1FA	Oct-32	10.2	31.4	8	52	3850	34
12.5L-16SL	E/10	FC1H8	Dec-32	11.4	33.4	10	44	3520	38
12.5L-16SL	F/12	FC1HA	Dec-32	11.4	33.4	10	52	3960	41
12.5L-16SL	G/14	FC1HC	Dec-32	11.4	33.4	10	56	4180	41

MAX SPEED 25 MPH

TYPE FI TIRES : LOADS CAN BE INCREASED BY 20% FOR SPEEDS UNDER 30 MPH.



Conventional Rib Implement (I-1)

The I-1 Conventional Rib Implement is a low cost, high quality farm wagon / implement tire. The I-1 implement's Multi-rib tread guards against side slippage and enables the tire to grip in any terrain and maintain directional stability. Smooth ribs eliminate stone drilling which can cause tire failure when under load.



CONVENTIONAL RIB IMPLEMENT (I-1) - TUBELESS

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
20.5/8-10	E	F/12	DE3M7	Oct-32	8.2	20.2	6	105	2275	20
26/12-12	D	B/4	FA3DW	Dec-32	12	26.2	10.5	20	1550	26
26/12-12	D	F/12	FA3DY	Dec-32	12	26.2	10.5	75	2750	35
7.50-14SL	B	B/4	FB1Y1	Oct-32	7.6	26.8	5.5	28	1360	18
4.00-15SL	A	B/4	FA3EA	Jun-32	4	23.5	3	44	785	10
5.00-15SL	A	B/4	FA3J1	Jul-32	5.1	24.9	3	36	965	13
6.40-15SL	A	B/4	FA3BE	Aug-32	6.4	26.9	4.5	32	1170	18
6.70-15SL	A	B/4	FC1X1	Aug-32	7.3	28	4.5	32	1280	19
7.60-15SL	A	C/6	FC113	Oct-32	7.6	28.5	5.5	40	1760	22
7.60-15SL	A	D/8	FC115	Oct-32	7.6	28.5	5.5	52	2090	22
10.00-15SL	C	D/8	FA395	13/32	11	33.7	8	40	3000	41
10.00-15SL	C	F/12	FA399	13/32	11	33.7	8	56	3960	47
7.50-16SL	F	D/8	FA3N5	13/32	7.98	29.89	5.5	44	2200	27
7.50-20SL	A	E/10	FA3BF	Nov-32	7.6	35	5.5	52	2600	33

Max Speed 25 mph

CONVENTIONAL RIB IMPLEMENT (I-1) - TUBE TYPE

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
5.90-15SL	A	B/4	FA3AH	Sep-32	6.3	26.6	4.5	36	1140	15
6.70-15SL	A	B/4	FC1X2	Aug-32	7.3	28	4.5	32	1280	16
6.70-15SL	A	C/6	FC1X4	Aug-32	7.3	28	4.5	44	1610	19
7.60-15SL	A	C/6	FC114	Oct-32	7.6	28.5	5.5	40	1760	19
7.60-15SL	A	D/8	FC116	Oct-32	7.6	28.5	5.5	52	2090	20
6.00-16SL	A	C/6	FA3L6	Jul-32	6.1	28.5	4	44	1520	18
6.50-16SL	A	C/6	FA3M4	Nov-32	7.1	28.8	4.5	44	1710	20
7.50-16SL	F	D/8	FA3N6	14/32	7.5	30	5.5	48	2710	24
9.00-16SL	A	E/10	FA3AW	Nov-32	9.2	33.4	6	52	3300	35
4.00-18SL	A	B/4	FA3AX	Jun-32	4.4	26.4	3	44	880	11
7.50-18SL	A	C/6	FA3W4	Oct-32	8	32.9	5.5	36	2040	23
4.00-19SL	A	B/4	FA3AE	18/32	4.5	29	3	44	940	13
7.50-20SL	A	C/6	FA3AM	Nov-32	7.6	35	5.5	36	2410	27

Max Speed 25 mph



Flotation Implement (I-2)

This quality tire has moderate traction with a proven diamond design for traction in all weather.



FLOTATION IMPLEMENT (I-2)									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
13.50-16.1SL	E/10	FA327	19/32	14	40	11	40	4940	79
13.50-16.1SL	F/12	FA329	19/32	14	40	11	44	5200	80
16.5L-16.1SL	C/6	FA833	18/32	16.4	42.25	14	24	3960	79
16.5L-16.1SL	E/10	FA837	18/32	16.4	42.25	14	36	5200	87

Traction Implement (I-3) Tubeless

The traction implement I-3 tire features an open curved bar design for excellent self-cleaning with a deep tread pattern for maximum traction and nylon construction for durability and long service life.



TRACTION IMPLEMENT (I-3)										
SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
5.00-15SL	D	B/4	TBA							
*7.60-15SL	D	B/4	FA512	17/32	7.9	30	5.5	28	1390	22
7.60-15SL	D	C/6	FA513	17/32	7.9	30	5.5	40	1930	27
12.5L-15SL	E	C/6	FA5E3	20/32	12.3	34.3	10	28	2540	46
12.5L-15SL	E	F/12	FA5E9	20/32	12.3	34.3	10	52	3860	53
16.5L-16.1SL	F	C/6	FA533	23/32	16.1	41.5	14	24	3960	105
16.5L-16.1SL	F	E/10	FA537	23/32	16.1	41.5	14	36	5200	108

* Tube Type



HF-3 Traction

This is a high flotation tire with a large diameter used for equipment that needs additional ground clearance and traction. The aggressive tread is suitable in multiple soil conditions.



FIG A

FIG B

H3 TRACTION										
SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
48/25.00-20	A	E/10	FB2DM	40/32	24.4	52	20.5	35	6150	307
48/31.00-20	B	F/12	FB2DN	40/32	30	52.5	26	40	6950	360

Farm Front (F-1 Single Rib)

The American Farmer F-1 Single Rib Farm Front Tire is used on vintage equipment and planting equipment. A single rib tracks in the rows to keep your equipment from wavering.



FARM FRONT (F-1 SINGLE RIB) TUBE TYPE									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
7.50-16SL	D/8	FA2N4	32/32	8.15	32	5.5	56	1710	29
10.00-16SL	D/8	FA2P6	24/32	11.2	35.15	8	44	2340	48
7.50-18SL	C/6	FA2W4	32/32	7.81	34.3	5.5	44	1610	32
7.50-20SL	C/6	FA2AM	32/32	8.48	37.5	5.5	44	1710	40
7.50-20SL	F/12	FA2DJ	32/32	8.34	37.5	5.5	72	2280	52
FARM FRONT (F-1 SINGLE RIB) TUBELESS									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
11.00-16SL	D/8	FA2T5	27/32	13.24	38.41	10	40	2600	47



Farm Front (F-2) Three Rib

A high quality farm equipment tire used on two-wheel drive tractors with a proven tread design. This economical tire with three rib design is great on hillsides with its ability to maintain traction.



FIG A

FIG B

FARM FRONT (F-2 TRIPLE RIB) TUBELESS										
SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
7.5L15SL	A	C/6	FA4B3	24/32	8	29.9	6	44	1430	32
9.5L15SL	A	D/8	FA4C5	30/32	9.5	31.2	7	48	1870	37
6.50-16SL	A	C/6	FA4M3	21/32	7	30.3	4.5	48	1230	26
7.50-16SL	A	C/6	FA4N3	23/32	7.9	32.1	5.5	44	1480	35
10.00-16SL	A	C/6	FA4P3	29/32	10.3	35.2	8	32	1930	49
10.00-16SL	A	D/8	FA4P5	29/32	10.3	35.2	8	44	2340	49
11.00-16SL	A	D/8	FA4T5	33/32	12.2	38.4	10	40	2600	68
FARM FRONT(F-2 TRIPLE RIB) TUBE TYPE										
SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
9.00-10SL	B	F/12	FA45A	17/32	9.2	27.4	6	60	2695	30
4.00-12SL	A	B/4	FA482	14/32	4.6	21.3	3	52	495	8
4.00-15SL	A	B/4	FA4AK	Jun-32	4.8	24.2	3	52	585	8
5.00-15SL	A	B/4	FC2J2	13/32	5.2	26.2	3	44	715	13
7.5L-15SL	A	C/6	FC2B4	24/32	8	29.9	6	44	1430	32
9.5L-15SL	A	D/8	FA4C6	30/32	9.5	31.2	7	48	1870	37
11L-15SL	A	D/8	FC2D6	30/32	10.4	33.4	8	44	2090	46
5.50-16SL	A	B/4	FC2K2	17/32	6.1	28.5	4	40	855	18
5.50-16SL	A	C/6	FC2K4	17/32	6.1	28.5	4	56	1050	19
6.00-16SL	A	B/4	FC2L2	15/32	6.5	29.1	4	36	910	20
6.00-16SL	A	C/6	FC2L4	15/32	6.5	29.1	4	52	1140	21
6.50-16SL	A	C/6	FC2M4	21/32	7	30.3	4.5	48	1230	26
7.50-16SL	A	C/6	FC2N4	23/32	7.9	32.1	5.5	44	1480	35
7.50-16SL	A	D/8	FC2N6	23/32	7.9	32.1	5.5	56	1710	36
10.00-16SL	A	C/6	FC2P4	29/32	10.3	35.2	8	32	1930	49
10.00-16SL	A	D/8	FC2P6	29/32	10.3	35.2	8	44	2340	49
11.00-16SL	A	D/8	FC2T6	33/32	12.2	38.4	10	40	2600	68
7.50-18SL	A	C/6	FC2W4	25/32	7.9	33.9	5.5	44	1610	38
4.00-19SL	A	B/4	FA4AE	Sep-32	4.4	28.3	3	52	715	12
7.50-20SL	A	C/6	FA4AM	23/32	7.9	36.8	5.5	44	1710	44
9.00-10SL	B	F/12	FA45A	17/32	9.2	27.4	6	60	2695	30



Farm Front (F2M) Four Rib

The American Farmer F2M Farm Front Tire is a quality tire for two wheel drive tractors that won't tear up the turf and minimizes damage. This easy to steer offers better road and smooth surface handling along with being compounded for extra long life.



FARM FRONT (F-2 M FOUR RIB) - TUBELESS									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
11L15SL	D/8	FA6D5	29/32	10.9	31.8	8	44	2090	51
1000-16SL	D/8	FA6P5	28/32	11.3	34.9	8	44	2340	54
1100-16SL	D/8	FA6T5	31/32	12	37.6	10	40	2600	61
14L16.1SL	C/6	FA3Z3	32/32	13.9	38.4	11	28	2540	82
14L16.1SL	E/10	FA3Z7	32/32	13.9	38.4	11	44	3420	89

FARM FRONT (F-2 M FOUR RIB) TUBE TYPE									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
11L-15SL	D/8	FA6D6	29/32	10.9	31.8	8	44	2090	51
10.00-16SL	D/8	FA6P6	28/32	11.3	34.9	8.8	44	2340	54
11.00-16SL	D/8	FA6T6	31/32	12	37.6	10	40	2600	61
14L-16.1SL	C/6	FA3Z4	32/32	13.9	38.4	11	28	2540	75

Industrial Rib (F-3)



The Industrial Rib (F-3) tire is designed for steering axle service on tractors and backhoes in industrial service and features a 5 rib tread, deep saw tooth groove and wide footprint.

INDUSTRIAL RIB F-3										
SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
9.00-10SL	A	8	FA956	Nov-32	9.2	26.3	6	48	1570	22
9.00-10SL	A	10	FA958	Nov-32	9.2	26.3	6	60	1820	25
11L-15SL	D	10	FA9D7	16/32	11	31.8	8	52	2340	40
11L-15SL	D	14	FA9DB	16/32	11	31.8	8	68	2710	49
11L-16SL	E	10	FA4F7	16/32	11	33	8	52	2470	42
11L-16SL	E	14	FA4FB	16/32	11	33	8	72	2930	53
11.00-16SL	C	12	FA9T9	15/32	12.4	38.1	10	60	3420	53
14.5/75-16.1SL	B	10	FA46W	16/32	15.5	36.8	11	40	3200	65



Tractor (R-1)

The tread bar angle is placed for maximum traction. These Tractor (R-1) tires are designed and constructed for durability with nylon cord for a long service life.



FIG A



FIG B



FIG C

TRACTOR (R-1)

SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
16-Jul	A	B/4	FA1BL	28/32	7.01	29.2	6	26	893	22
16-Jul	A	C/6	FA1BW	28/32	7.01	29.2	6	40	1135	24
7-16 *	A	C/6	FA1EW	28/32	7.01	29.2	6	40	1135	24

DRIVE WHEEL (R-1) - TUBE TYPE

SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
18.4-16.1	C	C/6	FA1DA	40/32	18.4	44.8	16	16	2810	115
18.4-16.1*	C	D/8	FA1AL	40/32	18.4	44.8	16	20	2910	126
18.4-38	B	D/8	FA1DH	43/32	18.82	68.25	16	20	5360	235
20.8-38	B	D/8	FA1DV	43/32	20.8	70.5	18	18	6150	260

* Tubeless

Tractor (R-4)

R4 American Contractor Farm Equipment Tractor -These versatile tires are specially constructed with heavier carcass and tougher compounds for severe applications and used on back hoes, snow removal equipment and a wide variety of industrial tractors.



FIG C



FIG D

TRACTOR (R-4)

SIZE	FIG	PLY RATING	PRODUCT CODE	TYPE	TREAD DEPTH	OVERALL DIA	RIM WIDTH	OVERALL WIDTH	MAX INFLATION	MAX LOAD 25 MPH	WT
14.9-24	C	8	NC5E3	R4	33/32	48.6	13	14.9	30	5080	119
16.9-24	C	8	NC5F3	R4	35/32	51.5	15	16.9	28	5840	148
17.5L-24	C	8	NC5H3	R4	33/32	49.2	15	17.5	26	5360	139
17.5L-24	C	12	NC5H5	R4	33/32	49.2	15	17.5	34	4680	151
18.4-24	C	10	NC5J5	R4	36/32	54.2	16	18.4	30	7400	176
19.5L-24	C	10	NC5K5	R4	34/32	51.5	17	19.5	28	6600	186
19.5L-24	C	12	NC5K7	R4	34/32	51.5	17	19.5	34	7600	191
21L-24	C	12	NC5L7	R4	35/32	54.5	18	21	32	8550	236
16.9-28	D	10	NC575	R4	31/32	56.5	15	18.1	32	6800	172
16.9-28	D	12	NC577	R4	31/32	56.5	15	18.1	38	7550	174



American Logger LS-1

These are high-quality steel belted tires for forestry applications.

- * Advanced rubber compounds provide maximum resistance to cutting, chipping and punctures.
- * Proven tread angles direct snags away from tire reducing penetrations.
- * Deep self cleaning lugs for maximum traction and pulling power.
- * Four steel belts for maximum protection.
- * 25% deeper tread than LS-1 standard tires.
- * Rim protection to protect rim and bead area.



AMERICAN LOGGER – LS-1										
SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
18.4-26	C	10	NF2A6	LS1	51/32	58.8	16	30	7950	264

American Logger LS-2

The American Logger LS-2 tires have four steel belts for forestry applications with advanced rubber compounds that provide maximum resistance to cutting, chipping and punctures. The proven tread angles direct snags away from tire reducing penetrations.

- * Deep self cleaning lugs for maximum traction and pulling power.
- * 25% deeper tread than LS-1 standard tires.
- * Rim protection to protect rim and bead area.



AMERICAN LOGGER – LS-2										
SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
23.1-26	B	10	NF146	LS2	67/32	64.8	20	25	10000	573
23.1-26	B	16	NF14C	LS2	67/32	64.8	20	40	13750	600
28L26	B	12	NF168	LS2	72/32	64.72	25	25	11600	658
28L26	B	14	NF16A	LS2	72/32	64.72	25	30	13100	658
28L26	B	16	NF16C	LS2	72/32	64.72	25	35	14325	658
24.5-32	B	16	NF18C	LS2	68/32	72	21	35	15400	639
30.5L32	B	16	NF1CB	LS2	70/32	72.5	27	30	16400	788
30.5L32	B	20	NF1AA	LS2	70/32	72.5	27	35	17950	821
18.4-34	B	10	NF1N6	LS2	64/32	66.8	16	30	8950	414



Skid Steer Tires

Skid Steer Tires for heavy-duty construction, agriculture and industrial uses.



FIG A

FIG B

SKID STEER								
SIZE	FIG	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	WEIGHT
10-16.5NHS *	A	6	DB3D4	32/32	10.66	30.59	7.25	66
10-16.5NHS *	A	8	DB3DM	32/32	10.66	30.59	7.25	67
10-16.5NHS +	A	10	DB3DN	32/32	10.66	30.59	7.25	69
12-16.5NHS *	A	8	DB3DJ	40/32	13	32.9	9.75	91
12-16.5NHS *	A	10	DB3DL	40/32	13	32.9	9.75	93
12-16.5NHS +	A	12	DB3DP	40/32	13	32.9	9.75	96
32/12-16.5NHS	A	12	DB3DY	32/32	11.6	34	9.75	95
10-16.5 NHS	B	10	TBA	26/32				
12-16.5 NHS	B	12	TBA	29/32	14.46	32.90	9.75	91

* Non-stocking Item

+ Steel Belted Available