

## PREMIUM SKID TRAX

### Heavy Duty Sidewall with Rim Guard

The Premium Skid Trax is a severe service skid steer tire that targets vehicles at above-ground mines and rock quarries. The tubeless, nylon tire features a heavy-duty sidewall with Rim Guard.



Size	Code	TD	TW	O.D.	C.S.	Rim	5 MPH		10 MPH		Wgt
							Air	Load	Air	Load	
10-16.5/10	SKD-30	37	9.5	31.3	11	8.25x16.5	75	4270	75	3730	78
12-16.5/12	SKD-32	40	11.3	32.9	12.8	9.75x16.5	80	6320	80	4990	108

## PREMIUM RADIAL SKID TRAX

### Tubeless -- Nylon -- Steel with Nylon Overlays



Size	Code	TD	TW	O.D.	C.S.	Rim	5 MPH		10 MPH		Wgt
							Air	Load	Air	Load	
10R16.5/8	RSK-40R	25	8.7	30.4	10.8	16.5x8.25	65	3970	65	3085	74
12R16.5/10	RSK-50R	30	10.1	32.9	13	16.5x9.75	70	5678	70	4410	90

## ULTRA SKID

Heavy Duty Sidewall with Rim Guard  
Tubeless - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim	5 MPH		10 MPH		Wgt
							Air	Load	Air	Load	
10-16.5/10	SKD-74	22	9.7	30.6	10.8	8.25x16.5	75	4720	75	3730	54
12-16.5/12	SKD-76	26	12.1	33.3	13.1	8.25x16.5	80	6320	80	4990	73

## TRAC SERVICE

Tubeless - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim	Max Infl.	Max Load	Wgt
6.00-16/10	IND-70	15	5.4	29	6.6	4.50x16	75	1920	28

\* Tire used inside Skid Steer Track

## SKID STEER PLUS

Heavy Duty Sidewall with Rim Guard  
Tubeless -- Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim	5 MPH		10 MPH		Wgt	Design
							Air	Load	Air	Load		
10-16.5/8	SKD-15	21	9.5	30.4	10.3	8.25x16.5	60	4140	55	3270	49	B
12-16.5/10	SKD-16	21	10.5	31.9	12.6	9.75x16.5	65	5600	65	4425	67	B
14-17.5/10	SKD-13	25	11.5	36.6	14.2	10.5x17.5	55	6580	55	5410	94	A
14-17.5/14	SKD-14	25	11.5	36.6	14.2	10.5x17.5	80	8540	80	6747	109	A
15-19.5/8	SKD-24	26	13.5	40.4	15.9	11.75x19.5	40	7250	40	5727	144	A
15-19.5/12	SKD-25	26	13.5	40.4	15.9	11.75x19.5	60	9190	60	7260	157	A
15-19.5/14	SKD-26	26	13.5	40.4	15.9	11.75x19.5	70	10060	70	7947	162	A
31x15.50-15/8	SKD-33	24	12.6	31.9	15.4	13x15	45	4361	45	3643	72	A
33x15.50-16.5/12	SKD-35	26	12.5	33.2	15.1	12x16.5	60	6835	60	5710	87	A

## SKID STEER

Tubeless -- Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim	5 MPH		10 MPH		Wgt
							Air	Load	Air	Load	
10-16.5/6	SKD-04	21	9.5	30.4	10.3	8.25X16.5	45	3500	45	2765	46
12-16.5/8	SKD-05	21	10.5	32.4	12.2	9.75X16.5	50	4810	50	3800	60
23x8.50-12/4	SKD-01	15	7.1	22.8	8.2	7X12	35	1470	35	1160	19
23x8.50-12/8	SKD-20	15	7.1	22.8	8.2	7X12	65	2105	65	1663	22
23x10.50-12/8	SKD-36	15	9.1	22.8	10.2	8.5x12	50	2130	50	1680	26
25x8.50-14/6	SKD-34	17	7.4	25.6	8.5	7x14	50	2130	50	1680	30
27x8.50-15/4	SKD-02	16	7.2	26.9	8.4	7X15	35	1840	35	1453	29
27x8.50-15/6	SKD-21	16	7.2	26.9	8.4	7X15	55	2400	55	1895	32
27x8.50-15/8	SKD-19	16	7.2	26.9	8.4	7X15	60	2875	60	2402	34
27x10.50-15/6	SKD-03	16	8.4	27.2	10.2	8.50X15	40	2480	40	1960	33

## OMNI TRAX

Tubeless -- Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim	Air	Load	Wgt
26x12.00-12/10	DDD-22	19	10.4	25.4	12.3	10.5X12	60	3380	35
31x15.50-15/8	DDD-20	24	14.2	31.8	14.7	13X15	45	2760	57
31x15.50-15/10	DDD-21	24	14.2	31.8	14.7	13X15	60	3200	59

10 M.P.H. Max. Speed on 12"

30 M.P.H. Max. Speed on 15"

## DITCH DIGGER

Tubeless -- Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim	Air	Load	Wgt
23x10.50-12/4	DDD-15	20	9.8	23	9.9	8.5X12	20	1340	23
26x12.00-12/6	DDD-03	19	10.5	25	12.3	10.5X12	30	2250	27
26x12.00-12/8	DDD-11	19	10.5	25	12.3	10.5X12	50	3020	30
26x12.00-12/10	DDD-13	19	10.3	25	12.3	10.5X12	60	3380	34
29x12.50-15/6	DDD-09	21	12	29.4	12.5	10X15	30	1680	46
31x15.50-15/8	DDD-02	24	14.4	31.5	14.7	13X15	45	2760	60

10 M.P.H. Max. Speed on 12"

30 M.P.H. Max. Speed on 15"

**TURF HUGGER**

Tubeless -- Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
20x8.00-10/4	DDD-30	10	7.6	20	8.1	6x10			24	895	13
26x12.00-12/6	DDD-01	12	10	25.4	11.2	10.5X12			30	2250	29
31x15.50-15/8	DDD-04	13	14.3	30.6	14.7	13X15			45	2760	59

10 M.P.H. Max. Speed on 12"

"30 M.P.H. Max. Speed on 15"

## GRADER - EARTHMOVER - LOADER DOZER



### E2/G2//L2 Tubeless -- Nylon

Size	Code	TD	TW	O.D.	C.S.	Rim			Max	Max	Wgt	Design
									Air	Load		
10.00-24/12 *	GRT-44	24	8.5	44.5	10.9	8X24			45	4350	107	B
13.00-24/12 *	GRT-12	29	10.5	50.1	13.3	8X24			44	6000	134	A
13.00-24/14 *	GRT-47	29	10.5	50.1	13.3	8X24			51	6800	140	A
14.00-24/12 *	GRT-07	31	11.5	52.8	14.1	8X24			36	6800	169	A
14.00-24/16 *	GRT-10	31	11.5	52.8	14.1	8X24			51	8050	181	A
16.00-24/16 *	GRT-31	35	12.8	57.5	17.2	10X24			44	9900	259	A
12.00-24/12 **	GRT-19	27	10.6	48	12.2	8X24			75	11700	125	C
13.00-24/16 **	GRT-55	29	10.5	50.1	13.3	8X24			87	14300	157	A
15.5-25/12 **	GRT-13	29	12.5	50.1	15.3	12X25			58	12300	171	A
17.5-25/12 **	GRT-05	31	13.4	53.5	17.6	14X25			51	13600	186	A
17.5-25/16 **	GRT-25	31	13.4	53.5	17.6	14X25			69	16100	187	A
20.5-25/12 **	GRT-21	35	16.5	58.5	20.5	17X25			36	14800	246	A
20.5-25/16 **	GRT-33	35	16.5	58.5	20.5	17X25			51	18200	266	A
23.5-25/12 **	GRT-50	40	23.2	64.6	23.3	19.5X25			33	17600	444	A
23.5-25/16 **	GRT-51	40	23.2	64.6	23.3	19.5X25			44	20900	507	A

\* 25 M.P.H. Max. Speed. All loads & Air. @ G-2 application

\*\* 5 M.P.H. Max. Speed. All loads & Air. @ L-2 application

## INDUSTRIAL TRACTOR TIRES



**R-4**  
Tubeless -- Nylon

Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt	Design
10.5x80-18/10	RTR-50	30	9	35.3	11.2	9X18			54	4265	78	A
10.5x80-18/12	RTR-51	30	9	35.3	11.2	9X18			65	4940	78	A
12.5x80-18/12	RTR-53	31	11.3	39.2	12.9	9X18			54	5788	98	A
12.5x80-18/14	RTR-54	31	11.3	39.2	12.9	9X18			62	6600	98	A
14.9-24/8	RTR-21	33	14.5	48.7	14.6	12X24			30	5080	120	B
14.9-24/12	RTR-32	33	14.5	48.7	14.6	12X24			38	6400	131	B
16.9-24/8	RTR-22	33	15.8	51.1	17.3	15X24			28	5840	152	B
16.9-24/10	RTR-30	33	15.8	51.1	17.3	15X24			32	6400	157	B
16.9-24/12	RTR-35	33	15.8	51.1	17.3	15X24			38	7150	165	B
17.5L-24/8	RTR-20	32	16.8	49.5	17.3	15X24			26	5360	145	B
17.5L-24/10	RTR-31	32	16.8	49.5	17.3	15X24			32	6150	150	B
18.4-24/10	RTR-28	28	16.5	54.5	18.2	16X24			30	7400	183	B
18.4-24/12	RTR-36	28	16.5	54.5	18.2	16X24			32	8250	192	B
19.5L-24/10	RTR-23	37	18.2	51.6	19.7	15X24			28	6600	194	B
19.5L-24/12	RTR-24	37	18.2	51.6	19.7	15X24			34	7600	200	B
21L-24/12	RTR-25	37	19.7	53.9	21.1	18X24			32	8550	254	B
16.9-28/8	RTR-27	37	15.7	55.4	17.2	15X28			28	6150	171	B
16.9-28/10	RTR-26	37	15.7	55.4	17.2	15X28			32	6800	176	B
18.4-28/10	RTR-29	28	16.3	58	18.2	16X28			30	7850	206	B

25 M.P.H. Max. Speed

## INDUSTRIAL TRACTOR TIRES

### R-3

Tubeless -- Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
13.6-16/6	RTS-01	23	11.50	39.2	13.6	12X16			28	2340	73
18.4-16.1/6	RTS-02	29	16.00	43.9	13.5	16X16.1			16	2540	124
14.9-24/6	RTS-05	25	11.80	48.6	14.9	13X24			20	3000	113
16.9-24/6	RTS-03	27	14.50	51	17.8	15X24			18	3420	134
16.9-24/10	RTS-09	27	14.50	51	17.8	15X24			28	4400	140
18.4-26/6	RTS-07	30	15.25	56.5	18.7	16X26			16	3960	167
18.4-26/12	RTS-10	30	15.25	56.5	18.7	16X26			32	5840	186
23.1-26/12	RTS-08	34	18.00	62.2	24.9	20X26			24	7150	338
12.4-28/4	RTS-06	22	9.20	48	12.9	11X28			16	1980	96
13.6-28/6	RTS-04	24	11.50	51	13.7	12X28			22	2830	108

25 M.P.H. Max. Speed

## INDUSTRIAL LUG

Tube Type--Nylon -- Flaps Included



Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
5.00-8/8	DTL-01	9	4.4	18.4	5.3	3.0X8			115	1830	11
18x7.0-8/16	DTL-25	21	5.5	18.1	6.6	4.33X8			145	4695	22
6.90-9/10	DTL-02	20	5	21	7	5.5X9			125	2820	20
6.50-10/10	DTL-03	21	5.5	23	7.2	5.0X10			115	3210	24
7.50-10/12	DTL-04	23	6.5	25.1	8	5.5X10			120	4300	39
7.00-12/12	DTL-05	22	6.3	26.8	7.5	5.0X12			125	4555	35
7.00-15/12	DTL-06	22	6.5	29.1	7.6	6.0X15			125	5275	41
7.50-15/12	DTL-07	23	7	31.5	8	6.0X15			115	5845	50
8.25-15/12	DTL-08	24	7.6	32.5	9.3	6.5X15			105	6595	58
28x9.0-15/12	DTL-27	20	8.5	27.9	8.9	7.0X15			120	6880	54
28x9.0-15/14	DTL-28	20	8.5	27.9	8.9	7.0X15			140	7530	57

5 M.P.H. Max Speed

\*All loads & Air. @ Industrial vehicle application

## COMPACTOR

Tubeless and Tube Type -- Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
7.50-15/6	IND-50		7.2	31.3	9.7	6.5X15			55	3900	43
7.50-15/6 (tbls)*	IND-51		7.2	31.3	9.7	6.5X15			55	3900	48
7.50-15/12	IND-52		7.2	31.3	9.7	6.5X15			110	5860	48
7.50-15/14	IND-53		7.2	31.3	9.7	6.5X15			125	6300	56

5 M.P.H. Max. Speed

\* Drop Center or Semi-Drop Center Rim

## EXPRESS ST BIAS

Tubeless -- Nylon



## SPECIAL TRAILER

Size	Code	TD	TW	O.D.	C.S.	Rim			Max	Max	Wgt
									Air	Load	
ST175/80D13/6	DST-01	11	4.5	24.1	7.5	5X13			50	1360	17
ST205/75D14/6	DST-03	11	5.4	26.2	7.9	5.5X14			50	1760	22
ST215/75D14/6	DST-04	11	5.7	26.8	8.5	6X14			50	1870	25
ST205/75D15/6	DST-05	11	6	27.9	8.5	5.5X15			50	1820	26
ST225/75D15/6	DST-07	11	6	28.5	8.7	6X15			50	2150	28
ST225/75D15/8	DST-08	11	6	28.5	8.7	6X15			65	2540	31

## EXPRESS ST RADIAL

Tubeless - Steel Belted



Size	Code	TD	TW	O.D.	C.S.	Rim			Air	Load	Wgt
ST175/80R13/6	DRT-51R	10	4.5	23.8	6.7	5X13			50	1360	20
ST205/75R14/6	DRT-53R	11	4.6	26.3	7.5	5.5X14			50	1760	25
ST215/75R14/6	DRT-54R	11	5	26.7	8.1	6X14			50	1870	27
ST205/75R15/6	DRT-55R	11	5	27.5	7.8	5.5X15			50	1820	28
ST205/75R15/8	DRT-56R	11	5	27.5	7.8	5.5X15			65	2150	31
ST225/75R15/8	DRT-58R	11	5.4	28.5	8.3	6X15			65	2540	35
ST225/75R15/10	DRT-59R	11	5.4	28.5	8.3	6X15			80	2830	34

## MEDIUM/HEAVY BIAS TRUCK



**HIGHWAY**

**HIGHWAY**

**CROSS LUG**

**TRACTION**

Tube Type - Nylon Flap Included

Size	Code	TD	TW	O.D.	C.S.	Rim	Single		Dual		Wgt	Design
							Air	Load	Air	Load		
7.50-20/14 (Set)	DEX-73	16	6	36.8	8.5	6.0X20	115	3640	105	4190	72	A
8.25-20/14 (Set)	DEX-71	19	6.3	38.4	9.3	6.5X20	115	4940	105	4410	75	A
9.00-20/14 (Set)	DEX-72	19	7	40	10.2	7.0X20	110	5675	100	5070	86	A
10.00-20/14 (Set)	DEX-70	13	7.5	41.5	10.9	7.5X20	100	6175	90	5355	89	A
11-22.5/14 TL ***	DEX-81	14	7.5	41.6	11	8.25X22.5	100	6175	90	5355	88	B
11-22.5/16 TL ***	DEX-60	14	7.5	41.6	11	8.25X22.5	115	6610	105	5840	90	B
11-24.5/12 TL***	DEX-09	17	7.5	42	11	8.25X24.5	85	5840	75	5070	97	B
7.5-20/14 (Set)	DEX-76	16	6	36.8	8.5	6.0X20	115	3640	105	4190	74	C
8.25-20/14 (Set)	DEX-77	19	6.3	38.4	9.3	6.5X20	115	4940	105	4410	77	C
9.00-20/14 (Set)	DEX-78	19	7	40.0	10.2	7.0X20	110	5675	100	5070	88	C
10.00-20/16	DEX-79	19	7.7	41.6	11	7.5X20	115	6610	105	5840	98	C
7.50-20/10	DEX-19	21	7.3	38.2	9.4	6X20	90	3530	80	3100	59	D
8.25-20/10	DEX-16	23	7.9	39.3	9.8	6.5X20	85	4080	75	3640	74	D
9.00-20/10	DEX-15	25	8.4	40.9	10.6	7X20	80	4675	70	4080	83	D
10.00-20/12	DEX-14	25	9.1	42.8	11.4	7.5X20	85	5510	75	4805	97	D

\*\*\*Flap not included (Set) Tire, Tube & Flap

## COMMERCIAL LIGHT TRUCK - BIAS



### Tubeless - Nylon

Size	Code	TD	TW	O.D.	C.S.	Rim	Single		Dual		Wgt	Design
							Air	Load	Air	Load		
6.70-15/6	TOR-66	15	5.1	29.1	7.5	5X15	45	1520	45	1355	30	A
7.00-15/8	TOR-30	14	6.1	29.6	7.9	5.5X15	60	2040	60	1820	27	E
6.50-16/6	TOR-14*	13	5.5	30	7.1	4.5X16	45	1610	45	1435	33	C
7.00-16/6	TOR-15*	14	5.8	30.8	8.1	5.5X16	45	1800	45	1580	38	C
7.50-16/10	TOR-32	14	6.3	31.7	8.5	6.0X16	75	2755	75	2470	34	E
7.50-16/8	TOR-04	18	6.4	32.2	8.7	6.0X16	60	2470	60	2150	39	B
7.50-17/8 (tt)	TOR-18*	15	6.4	34.4	9	6.0X17	75	2800	75	2460	45	C
7.50-17/10 (tt)	TOR-16*	15	6.4	34.4	9	6.0X17	90	3170	90	2780	45	C
7.50-17/10 (tt)	TOR-17*	22	6	34.2	8.8	6.0X17	90	3170	90	2780	44	B
8.00-16.5/8	TOR-70	14	6.3	26.6	8.5	6.75x16.5	60	2040	60	1825	30	A
8.75-16.5/8	TOR-71	14	7	29.4	8.8	6.75x16.5	60	2405	60	2095	33	A
8.75-16.5/10	TOR-76	14	7	29.4	8.8	6.75X16.5	80	2680	80	2405	36	A
9.50-16.5/8	TOR-72	15	7.5	31	9.6	6.75x16.5	60	2835	60	2470	39	A
9.50-16.5/10	TOR-73	15	7.5	31	9.6	6.75x16.5	75	3195	75	2835	41	A
10-16.5/8	TOR-59	15	7.6	30.2	10.6	8.25x16.5	60	2755	60	2470	44	D
12-16.5/12	TOR-74	15	8.8	32.2	12.2	9.75x16.5	75	4080	75	3640	58	A
12-16.5/14	TOR-75	15	8.8	32.2	12.2	9.75x16.5	90	4490	90	3950	62	A
8-17.5/8 LT	TOR-22	15	5.8	30.8	8	6.0X17.5	60	2470	60	2150	36	A
8-19.5/10	TOR-21	15	6.2	34.6	8.4	6.0X19.5	90	3195	80	2835	47	C

\* Torneil Brand

## NON-DIRECTIONAL TRUCK TIRE

Tubeless-Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim	Max		Wgt
							Air	Load	
9.00-16/8	tr-12	18	7.9	35.2	10.1	6.5Hx16	50	3030	53

## LOW PLATFORM TRAILER

A



B



Size	Code	TD	TW	O.D.	C.S.	Rim	Single		Dual		Wgt	Design
							Air	Load	Air	Load		
7-14.5/12 TL	TR-81	9	5.6	26.5	7.3	6X4738	85	2095	85	1845	25	A
8-14.5/14 TL	LPT-08	9	6.2	27.6	7.8	6X14.5	115	302	115	2660	27	A
9-14.5/14 TL	TR-83	12	7.2	38.5	9.5	7X14.5	115	3825	115	3370	44	A
7.50-15/14 TR	TR-84	14	5	30.7	8.5	6X15	120	3525	110	3085	45	B
8.25-15/14 TR	LPT-17	15	6.4	33.1	9.5	6X15	115	4080	105	3640	58	B
9.00-15/14	TR-86	16	6.6	35.9	10.2	7.5X15	110	4805	100	4190	62	B
10.00-15/16 TR	TR-87	18	7.5	36.8	11	7.5X15	115	5675	105	4940	73	B

## INDUSTRIAL MULTI-RIB

### F-3

Tubeless - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max	Max	Wgt
									Air	Load	
11L-15/10 SL	FT-46	16	9	31	10.5	8x15			52	2340	44
11L-16/10 SL	FT-47	16	9.3	31.2	10.4	8X16			52	2470	44
11L-16/12 SL	FT-53	16	9.3	31.2	10.4	8X16			64	2760	46
14.5/75-16.1/10 SL	FT-52	18	11.2	35.5	14.4	11X16.1			40	3200	85

25 M.P.H. Max. Speed

## FARMHAND A/P TRACTOR

### R-1

Tubeless - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Air	Load	Wgt
5-12/6	TAP-08	26	4.3	21	5	4X12			52	615	13
6-12/4	TAP-09	TIRE UNDER DEVELOPMENT									
6-14/6	TAP-12	28	5.2	24.7	6.1	5X14			42	825	21
6-16/6	TAP-10	28	5	27	5.9	5X16			42	935	22
7-16/6	TAP-01	32	6.1	29	7.5	6.5X16			36	1100	32
8-16/6	TAP-03	33	7	30.4	8.2	7X16			28	1360	36
9.5-16/6	TAP-06	37	9	33	9.5	8X16			30	1390	48

25 M.P.H. Max. Speed

## FARMHAND A/P TRACTOR

### R-1

Tubeless and tube type - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
8.3-24/6 TT	RF-03	31	7.9	38.8	8.3	7.0X24			34	1610	47
9.5-24/6 TT	RF-05	33	8.7	41.2	9.5	8.0X24			30	1870	59
11.2-24/6 TT	RF-07	36	10.7	42	11.5	10.0X24			26	2090	76
12.4-24/8 TT	RF-09	38	11.8	44	12.5	11.0X24			32	2830	88
13.6-24/8 TT	RF-11	42	13.4	47.8	14.3	12.0X24			28	3080	102
14.9-24/8 TT	RF-13	42	14	49.2	14.8	13.0X24			26	3250	118
11.2-28/6 TT	RF-15	32	10.4	46.9	11.1	10.0X28			26	2200	80
12.4-28/8 TT	RF-17	38	11.8	49.6	12.5	11.0X28			32	3000	99
13.6-28/28 TT	RF-19	42	12.5	52	13.2	12.0X28			28	3300	112
14.9-28/8 TT	RF-21	42	14.6	54.6	15.2	13.0X28			26	3740	120
16.9-28/8 TT	RF23	43	16.7	57	17.6	15.0X28			24	4300	151
16.9-30/10 TT	RF-25	43	16.9	59	17.6	15.0X30			28	4940	154
18.4-30/10 TT	RF-27	45	17.9	61	18.7	16.0X30			26	5520	202
18.4-34/10 TT	RF-29	45	18	64.1	18.4	16.0X34			26	6000	205
11.2-38/8 TL	RF31	36	10.7	57	11.2	10.0X38			32	2720	97
11.2-38/8 TT	RF-33	36	10.7	57	11.2	10.0X38			32	2720	98
12.4-38/8 TT	RF-57	42	11.8	58.8	12.5	11.0X38			32	3520	127
13.6-38/8 TT	RF-59	45	12.6	61.1	13.4	12.0X38			28	3740	157
15.5-38/10 TT	RF-35	45	14.8	61	15.4	14.0X38			30	4050	145
18.4-38/10 TT	RF-37	45	18	68	18.4	16.0X38			26	6400	229

## R-1 IRRIGATION

Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
11.2-24/4 TT (SET)	RF-39	36	10.8	42	11.5	10.0X24			18	1650	76
11.2-38/4 TT	RF-41	36	10.7	57	11.2	10.0X38			18	2090	93
14.9-24/6	RF-43	42	14	49.2	14.8	13.0X24			20	3000	112

## FARMHAND FRONT TRACTOR

### 3-RIB F2

Tubeless and Tube Type - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
4.00-12/4 TT	DFH-01	12	3.8	21	4.3	3.0X12			52	495	10
4.00-16/4 TT	DFH-03	12	3.8	28.3	4.4	3.0X19			52	715	12
5.00-15/4 TT	DFH-11	17	4.2	24.9	4.9	3.0X15			44	715	12
5.50-16/8 TT	DFH-13	17	4.9	27.4	5.4	4.0X16			64	1200	18
5.50-16/8 TT	DFH-15	17	4.9	27.4	5.4	4.0X16			64	1200	19
6.00-16/8 TT	DFH-17	17	6.2	28.8	6.6	4.0X16			68	1360	19
6.00-16/8 TT	DFH-59	17	6.2	28.8	6.6	4.0X16			68	1360	20
6.5-16/8 TT	DFH-21	17	6.4	28.8	6.7	4.5X16			60	1475	21
6.5-16/8 TL	DFH-61	17	6.4	28.8	6.7	4.5X16			60	1475	22
7.5-16/8 TT	DFH-25	22	7.6	31.4	8.3	5.5X16			56	1710	31
7.5-16/10 TL	DFH-27	22	7.6	31.4	8.3	5.5X16			68	190	33
7.5-18/8 TL	DFH-65	27	7.4	33	7.8	5.5X18			56	1870	37
7.5-20/6 TT	FT-15	32	6.4	35.9	7.9	5.5X20			44	1710	36
7.5L-15/6 TT	FT-30	26	6.9	29	8.4	6X15			44	1430	29
9.5L-15/8 TT	DFH-07	22	8.9	30.6	9.4	7.0X15			48	1870	38
11L-15/8 TT	DFH-09	25	9.5	32.1	10.8	8.0X15			44	2090	43
10.00-16/10 TT	DFH-37	28	8.9	34.1	10.2	8.0X16			56	2800	53
11.00-16/10 TT	DFH-45	28	10.5	37.2	11.2	10.0X16			48	2910	60
11.00-16/12 TL	DFH-47	28	10.5	37.2	11.2	10.0X16			60	3420	62

25 M.P.H. Max Speed

### 4-RIB F2

Tubeless and Tube Type - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
10.00-16/10 tl	DFH-67	28	9	34.6	10.3	8.0x16			56	2800	56
11.00-16/10 tt	DFH-49	28	10.6	37.7	11.2	10.0X16			48	2910	64
11.00-16/12 TL	DFH-51	28	10.6	37.7	11.2	10.0X16			60	3420	66
14L-16.1/10 TL	DFH-57	32	12.8	38.4	13.5	11.0X16.1			44	3420	101

25 M.P.H. Max. Speed

## FARM HAND IMPLEMENT

### I-1

Tubeless and Tube Type - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max Air	Max Load	Wgt
9.5L-14/8 TT	IF-01	8	8.8	29	9.4	7.0X14			44	2400	26.5
9.5L-14/8 TL	IF-03	8	8.8	29	9.4	7.0X14			44	2400	27
11L-14/8 TT	IF-15	8	9.8	29.4	10.8	8.0X14			36	2470	28
11L-14/8 TL	IF-17	8	9.8	29.4	10.8	8.0X14			36	2470	29
6.70-15/8 TT	IF-31	7	6	27.5	6.6	4.5X15			60	2010	18
6.70-15/8 TL	IF-33	7	6	27.5	6.6	4.5X15			60	2010	18
7.60-15/8 TT	IF-35	8	6.8	28.7	7.5	5.5X15			52	2090	23
7.6-15/8 TL	IF-37	8	6.8	28.7	7.5	5.5X15			52	2090	23
9.5L-15/8 TT	IF-05	11	9	30	9.8	7.0X15			44	2470	28
9.5L-15/8 TL	IF-07	11	9	30	9.8	7.0X15			44	2470	29
11L-15/8 TT	IF-09	11	9.9	31.2	10.8	8.0X15			36	2540	30
11L-15/8 TL	IF-11	11	9.9	31.2	10.8	8.0X15			36	2540	32
11L-15/12 TL	IF-13	11	9.9	31.2	10.8	8.0X15			52	3200	33
12.5L-15/12 TT	IF-23	11	11.1	12.1	12.1	10.0X15			52	3860	40
12.5L-15/12 TL	IF-25	11	11.1	12.1	12.1	10.0X15			52	3860	41
11L-16/10 TT	IF-19	11	9.9	10.8	10.8	8.0X16			44	3000	33
12.5L-16/10 TT	IF-27	11	11.2	12.3	12.3	10.0X16			44	3680	43
12.5L-16/14 TL	IF-29	11	11.2	12.3	12.3	10.0X16			56	4180	45

25 M.P.H. Max. Speed

**RM 823/826**

**E-3 / L-3**  
**E-4 / L-4 \***  
Tubeless - Nylon



Size	Code	TD	TW	O.D.	C.S.	Rim			Max	Max	Wgt
									Air	Load	
14.00-24/24 **	RM-17	31	12.9	50.3	14.2	10X24			123	20900	230
17.5-25/16	RM-01	38	15.4	53.2	17.5	14X25			69	16,100	300
20.5-25/16	RM-02	40	18.1	58.7	20.5	17X25			51	18,200	382
20.5-25/20	RM-04	40	18.1	58.7	20.5	17X25			65	20,900	406
23.5-25/16	RM-03	45	20.7	63.6	23.4	19.5X25			44	20,900	507
23.5-25/20	RM-05	45	20.7	63.6	23.4	19.5X25			54	24,000	613
26.5-25/20	RM-13	48	24	70.8	26.6	22X25			51	29,100	793
29.5-25/28	rm-81	48	29.5	73.8	29.6	25x25			47	33,100	1061
29.5-28/28	RM-82	48	29.5	77.8	29.6	25X25			62	38,600	1301
16.00-25/28	RM-11	38	14.2	58.7	16.9	11.25X25			109	25,400	430
18.00-25/28	RM-12	40	16.5	63.6	19.5	13X25			94	30,000	560

\*\* Tube Type

## LIGHT TRUCK RADIAL

### COYOTE A/P

Raised black Lettered - Polyester-  
Steel Belted Radia LT Tubeless



Size	Code	TD	TW	O.D.	C.S.	Rim			Max	Max	Wgt
									Air	Load	
LT 305-/85R-16/10	COY-11R	16	9	36	12.4	8X16			69	3640	72

## MINING

TUBELESS - NYLON

A

B



Size	Code	TD	TW	O.D.	C.S.	Rim			Max	Max	Wgt	Design
									Air	Load		
14-17.5/10 ML	TR-90	24	10	35	12.5	10.5X17.5			70	4800	83	B
14-17.5/10 ML	TR-91	18	11	35.3	14	10.5X17.5			70	4800	70	A

55 M.P.H. Max Speed

**MINE KING**

Tubeless and Tube Type -Nylon



Size	Code	PLY	SKID TREAD		O.D	RIM	C.S.	STATIC	
			DEPTH	WIDTH				Max INFL	Max Load
27x15-10 TT	MIN-43	24	26	14	26.91	13x10	15.23	150	14870
8.25-15 TT	MIN-35	24	28	7.8	33.31	6.5x15	9.8	135	12073
10.00-15 TT	MIN-47	24	28	9.3	35.7	7.5x15	10.95	150	17550
32x12-15 TT	MIN-33	24	32	11	32.17	11x15	13.58	150	16400
32x15-15 TT	MIN-49	24	32	13.1	32.16	11.5x15	14.35	150	19000
32x15-15 TL	MIN-50	28	32	13.1	32.16	11.5x15	14.35	150	19000
35x15-15 TL	MIN-37	32	32	12.2	34.71	11x15	14.22	150	21490
38x16-15 TL	MIN-39	36	28	13.6	37.63	11x15	15.75	150	30750
42x13-20 TL	MIN-30	32	28	11	41.7	9 to 10x20	13.12	140	23750
12.00-20 TT	MIN-45	28	28	11.3	44	8.25x20	13	150	26020
14.00-20 TT	MIN-41	32	33	13	49.54	10x20	15.65	150	35795

**CLASSIC IV**

Tubeless - Polyester



Size	Code	TD	TW	O.D.	C.S.	Rim	WSW Width	Max Air	Max Load	Wgt
G78-14/4	DC-431	11	5.3	27.2	8.7	6x14	3.5"	32	1620	25
G78-15/4	DC-441	11	5.3	28	8.1	6x15	3.25"	32	1620	26
L78-15/4	DC-451	11	5.7	29.5	9.1	6x15	4.5"	32	1970	30

**COLUMBIA DELUXE**

Size	Code	TD	TW	O.D.	C.S.	Rim	Max Air	Max Load	Wgt
6.00-16/4	PAS-25								16