

SUPER SWAMPER TSL



The Super Swamper TSL with the patented TSL tread design offers unsurpassed traction under the toughest of conditions. Nine years of developing and testing produced the ultimate tire tread design. Short, intermediate and long massive lugs are uniquely arranged, each proportioned and spaced to bite quickly and to self-clean rapidly. The overall design gives today's on-and-off-road driver a tire that is both directionally and laterally stable; unmatched in performance. This is an extremely aggressive design that requires strict attention to air pressure when run on the highway.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
SAM-06	28x8.50-14LT	4	20	7.00	27.40	9.00	14x6.5	30	1310	31
SAM-25	29x8.50-15LT	4	25	7.10	28.50	8.90	15x6	35	1415	33
SAM-12	31x10.50-15LT	6	24	9.00	31.30	10.20	15x8	45	2250	48
S-203	12-15LT	6	21	10.00	32.10	12.00	15x10	30	2250	51
SAM-38	32x9.50-15LT	6	26	8.50	32.30	9.40	15x7	45	2330	50
SAM-13	33x12.50-15LT	8	24	10.20	33.70	12.40	15x10	45	2820	60
SAM-32	15/35-15LT	6	25	12.50	34.80	14.30	15x10	45	2850	82
SAM-52	Q78-15LT	6	27	9.50	35.50	10.80	15x6.5-8	40	2750	65
SAM-26	36x12.50-15LT	8	24	10.50	36.30	13.50	15x10	45	2820	65
SAM-94	38x12.50-15LT	6	23	10.00	37.80	12.80	15x10	45	2700	72
SAM-36	16/38.5-15LT	6	25	13.00	38.20	15.40	15x10	30	2410	90
SAM-34	15/39.5-15LT	6	25	13.00	39.40	15.30	15x10	30	2410	97
SAM-23	15/42-15LT	6	27	13.00	42.00	15.30	15x10	30	2685	107
SAM-42	18.5/44-15LT	6	27	14.40	44.20	17.50	15x12	30	2855	121
SAM-39	9/32-16LT	6	26	8.50	32.00	8.80	16x6.5-8	45	2330	52
SAM-40	9/32-16LT	10	26	8.50	32.00	8.80	16x6.5-8	75	3042	55
SAM-17	13/33-16LT	8	24	10.20	33.50	12.30	16x10	45	2930	62
SAM-53	Q78-16LT	6	27	9.50	35.50	10.80	16x6.5-8	40	2580	66
SAM-27	13/36-16LT	6	24	10.40	35.90	12.70	16x10	45	2850	68
SAM-95	13/38-16LT	6	23	10.00	37.80	12.70	16x10	45	2700	73
SAM-87	15/42-16LT	6	27	13.0	42.0	15.2	16X10-12	30	2685	102
S-204	12-16.5	8	24	9.00	32.00	11.93	16x9.75	45	3000	52
SAM-19	33x12.50-16.5LT	8	24	10.10	33.50	12.20	16.5x9.75	45	2930	61
SAM-33	15/35-16.5LT	6	25	12.50	34.80	14.20	16.5x9.75	45	2850	76
SAM-41	15/35-16.5LT	10	25	12.50	34.80	14.20	16.5x9.75	75	3880	86
SAM-28	36x12.50-16.5LT	8	25	10.40	35.90	12.60	16.5x9.75	45	2930	66
SAM-96	38x12.50-16.5LT	6	23	10.00	37.80	12.60	16.5x9.75	45	2700	73
SAM-37	16/38.5-16.5LT	6	25	13.00	38.20	15.40	16.5x9.75	30	2410	89
SAM-35	15/39.5-16.5LT	6	25	13.00	39.40	15.00	16.5x9.75	30	2410	92
SAM-71	15/39.5-16.5LT	10	25	13.00	39.40	15.00	16.5x9.75	60	3840	95
SAM-24	15/42-16.5LT	6	27	13.00	42.00	15.10	16.5x9.75	30	2485	105
SAM-43	18.5/44-16.5LT	6	27	14.40	44.20	17.00	16.5x12	30	2855	120
SAM-64	15/39.5-17LT	6	25	12.50	39.42	14.38	17x10-12	30	2410	95
SAM-88	15/42-17LT	6	27	13.00	42.00	14.90	17x10-12	30	2680	

SUPER SWAMPER TSL / SX



The Super Swamper TSL/SX was designed for extremely tough off road conditions where sidewall strength and protection is needed to withstand the severe scuffing from running in ruts and snagging roots and rocks. This tire has a strong nylon or polyester bias ply body with dual belts under the tread and wrap-around lugs. The sidewall lugs not only protect the sidewall but also provide extra traction when climbing out of ruts.

Product # B/W	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
S-211/201	29x10.50-15LT	4	22	9.10	29.00	10.50	15x8	30	1495	40/40
S-212/202	30x11.50-15LT	4	21	9.70	29.60	12.00	15x10	30	1700	44/44
SAM-59*	31x13.50-15LT	6	24	11.60	30.75	13.00	15x8-10	30	1965	58
SAM-77	32x11.50-15LT	6	23	9.90	31.60	11.40	15x8	45	2530	55
SAM-50	33x15.50-15LT	6	23	12.30	33.10	15.20	15x10-12	30	2415	71
SAM-67	35x15.50-15LT	6	25	13.10	34.80	15.40	15x10-12	30	2800	85
S-205/SAM-56	36x12.50-15LT	6	22	10.30	35.90	13.30	15x8.5-10	30	2720	72/78
SAM-61	38x12.50-15LT	6	23	10.00	37.40	13.40	15x10	45	2700	84
SAM-75	38.5x14.50-15LT	6	23	12.30	38.30	15.40	15x10-12	30	3370	89
SAM-78	32x11.50-16LT	6	24	10.00	31.50	10.10	16x8	45	2435	58
SAM-51	33x15.50-16.5LT	6	23	12.30	33.10	14.80	16.5x9.75-12	30	2510	66
SAM-68	35x15.50-16.5LT	6	25	13.10	34.80	15.10	16.5x9.75-12	30	2915	76
SAM-86	36x12.50-16LT	10	22	10.30	35.90	13.00	16x8.5-10	60	3640	79
SAM-57	36x12.50-16.5LT	6	22	10.30	35.90	13.00	16.5x9.75	30	2850	74
S-206/SAM-65	36x12.50-16.5LT	10	22	10.30	35.90	13.00	16.5x9.75	60	3640	75/80
SAM-93	38x12.50-16.5LT	6	25	9.80	38.50	13.00	16.5x9.75	45	2700	83
SAM-98+	38x12.50-16.5LT	10	25	10.00	37.60	13.10	16.5x9.75	75	3845	85
SAM-76	38.5x14.50-16.5LT	6	23	12.30	38.50	15.30	16.5x9.75-12	30	3540	84
S-207	36x12.50-17LT	10	22	10.00	36.30	12.80	17x10	60	3800	75

*Steel Belted/Polyester

+All Nylon Construction - No Steel Belts in the 10 ply tire

SPECIAL SERVICE SUPER SWAMPER TSL



Super Swamper TSL... designed primarily for light trucks such as Toyotas and Jeeps. Also great for Duallys in tire combinations such as 9/34-16 paired in the rear and 13/33-16's in front or 34x9.50-16.5 paired in the rear and 33x12.50-16.5's in front.

Make sure to double check the weight of your vehicle to ensure these tires have enough carrying capacity for the vehicle.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
SAM-14	34x9.50-15LT	6	27	8.00	33.80	9.50	15x7	45	2370	54
SAM-21	9/34-16LT	6	27	8.00	33.80	9.10	16x6.5	45	2370	56
SAM-22	34x9.50-16.5LT	6	27	8.00	33.80	9.00	16.5x6.75	45	2370	54

SUPER SWAMPER LTB



What is the Super Swamper LTB...

The Super Swamper LTBs are in the same basic Three Stage Lug design as the famous Super Swamper TSL's but a little more aggressive. The large lug is offset more to the outside which gives the tire superb traction. It is in bias ply construction which allows for the more aggressive lugs and very strong sidewalls to better resist the rigors of hard off-roading. The bias construction reduces the chances of sidewall splitting when run off road at low air pressure. There are seven sizes available.... sizes which are not available in the regular TSL line.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
LTB-01	31x11.50-15LT	6	22	9.75	31.00	10.90	15x8	45	2340	49
LTB-04	33x13.50-15LT	6	22	11.30	32.80	13.00	15x10	30	2270	62
LTB-07	34x10.50-15LT	6	22	9.25	33.60	11.20	15x8.5	45	2655	58
LTB-201	17/47-15LT	6								
LTB-02	31x11.50-16LT	8	22	9.75	31.00	10.30	16x8	60	2650	49
LTB-05	33x13.50-16LT	8	22	11.30	32.80	12.60	16x10	45	2755	61
LTB-08	34x10.50-16LT	8	22	9.25	33.60	10.70	16x8	60	3195	59
LTB-200	17/47-16.5LT	6	27	14.33	46.98	17.01	16.5x10-14	30	2830	
LTB-09	34x10.50-17LT	8	22	9.30	33.80	10.30	17x8	60	3085	58

SUPER SWAMPER RADIAL / TSL



The Super Swamper Radial is the most aggressive light truck tire ever developed. It is designed for a very smooth ride at surprisingly low noise level.

Product # B/W	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
SAM-69R	LT225/85R14	6	19	6.60	28.70	8.80	14x6	50	1930	36
SAM-70R	LT215/85R15	6	19	6.60	28.70	8.60	15x6	50	1875	35
SAM-81R/813R*	30x10.50R15LT	6	21	7.90	29.70	10.20	15x8	50	2070	49/48
SAM-82R/823R*	31x9.50R15LT	6	19	7.20	30.70	9.60	15x7.5	50	2160	46/45
SAM-44R	32x10.50R15LT	6	21	9.00	32.10	10.50	15x7	50	2370	52
SAM-83R/833R*	33x10.50R15LT	6	21	7.90	32.70	10.60	15x8.5	50	2620	55/54
SAM-79R/793R*	33x12.50R15LT	6	21	9.40	32.70	12.70	15x10	35	2225	56
SAM-73R	36x12.50R15LT	6	21	9.00	36.20	12.70	15x10	35	2600	67
SAM-47R	36x14.50R15LT	6	21	11.50	35.60	15.10	15x10	35	2910	79
SAM-90R	38x15.50R15LT	6	21	11.80	37.10	15.20	15x10	35	3010	90
SAM-97R	LT265/80R16	8	21	9.00	32.20	10.50	16x7	65	3085S/2835D	59
SAM-89R	36x12.50R16LT	10	21	9.00	35.90	12.60	16x10	65	3640	76
SAM-66R	36x14.50R16LT	10	21	11.50	36.00	14.30	16x10	65	3640	93
SAM-54R	33x12.50R16.5LT	10	21	9.40	32.70	11.50	16.5x9.75	65	3525	64
SAM-92R	36x14.50R16.5LT	10	21	11.50	36.00	14.30	16.5x9.75	65	3640	92
SAM-55R	38x15.50R16.5LT	10	21	11.50	37.60	14.30	16.5x9.75	65	3640	99

*Minimum Run 200 on White Letter Tires



SSR SERIES SUPER SWAMPER RADIAL / TSL

The SSR Series of Super Swamper Radial/TSL tires is the next generation of light truck radial tires. This series has many of the OEM sizes for Sport Utility Vehicles and 4 Wheel Drive light trucks who do not want to modify their vehicles but still need the performance of Super Swampers. The design incorporates a slightly tighter tread pattern, siping for wet pavement traction and icy conditions, greater sidewall protection with traction features and is quieter running.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
SSR-02R	27x9.50R14LT	6	21	7.90	27.50	9.50	14x6.5-8.5	50	1585	37
SSR-03R	27x9.50R15LT	6	21	7.90	27.50	9.50	15x6.5-8.5	50	1495	39
SSR-05R	29x11.50R15LT	6	21	9.70	29.50	11.50	15x8-10	50	1965	54
SSR-07R	31x10.50R15LT	6	21	9.00	31.50	10.50	15x7-9	50	2250	57
SSR-09R	31x12.50R15LT	6	21	10.30	31.40	12.50	15x8.5-10	35	1800	63
SSR-12R	32x11.50R15LT	6	21	10.00	32.50	11.50	15x8-10	50	2530	62
SSR-16R	33x12.50R15LT	6	21	10.60	33.40	12.50	15x8.5-10	35	2225	67
SSR-20R	33x14.50R15LT	6	21	12.40	33.50	14.50	15x10-12	35	2365	76
SSR-40R	35x10.50R15LT	6	21	9.00	35.00	11.60	15x7-9	50	3000	70
SSR-24R	35x12.50R15LT	6	21	10.60	35.30	12.50	15x8.5-10	35	2555	75
SSR-28R	35x14.50R15LT	6	21	12.20	35.20	14.50	15x10-12	35	2680	83
SSR-43R	37x12.50R15LT	6	21	10.60	36.80	13.50	15x10	35	2895	78
SSR-65R	38x15.50R15LT	6	21	13.10	38.20	15.30	15x10-12	65	3000	95
SSR-50R	31x12.50R16LT	10	21	10.60	31.60	12.00	15x10	65	2755	71
SSR-51R	32x11.50R16LT	10	21	9.60	32.70	11.90	16x8	80	3305	69
SSR-31R	LT265/70R16	8	21	9.00	31.50	10.70	16x7-8	65	*2835S/2600D	66
SSR-38R	LT285/75R16	8	21	9.40	33.90	11.40	16x8	65	*3305S/3000D	73
SSR-35R	LT305/70R16	8	21	10.40	33.90	12.40	16x8-10	50	*2910S/2680D	81
SSR-52R	33x12.50R16LT	10	21	10.60	33.40	12.30	16x10	65	3195	76
SSR-54R	33x14.50R16LT	10	21	12.30	33.40	13.90	16x12	65	3415	86
SSR-41R	35x10.50R16LT	8	21	9.00	35.30	11.10	16x7-9	65	3415	76
SSR-58R	35x12.50R16LT	10	21	10.60	35.30	12.60	16x8.5-10	65	3640	87
SSR-69R	35x14.50R16LT	10	21	12.20	35.20	14.50	16x10-12	65	3640	93
SSR-44R	37x12.50R16LT	10	21	10.60	36.90	13.00	16x10	65	3640	90
SSR-66R	38x15.50R16LT	10	21	13.10	38.20	15.30	16x10-12	65	3640	105
SSR-53R	33x12.50R16.5LT	10	21	10.60	33.40	12.10	16.5x9.75	65	3525	77
SSR-55R	33x14.50R16.5LT	10	21	12.30	33.40	13.70	16.5x9.75-12	65	3640	87
SSR-57R	35x12.50R16.5LT	10	21	10.60	35.30	12.50	16.5x9.75	65	3640	86
SSR-59R	35x14.50R16.5LT	10	21	12.20	35.20	14.50	16.5x9.75-12	65	3640	93
SSR-45R	37x12.50R16.5LT	10	21	10.60	36.90	13.00	16.5x9.75	65	3970	89
SSR-67R	38x15.50R16.5LT	10	21	13.10	38.20	14.80	16.5x9.75-12	65	3640	104
SSR-15R	32x11.50R17LT	10	21	10.00	32.60	11.20	17x8-10	80	3195	66
SSR-70R	LT265/70R17	10	21	9.00	32.50	10.70	17x7-9	50	*2740S/2270D	68
SSR-85R	33x12.50R17	10	21	10.60	33.40	11.90	17x8.5-11	65	3085	72
SSR-42R	35x10.50R17LT	10	21	9.00	35.30	11.60	17x7-9	80	3640	73
SSR-60R	35x12.50R17LT	10	21	10.60	35.30	12.30	17x8.5-11	65	3640	85
SSR-46R	37x12.50R17LT	10	21	10.60	36.90	13.00	17x10	65	3640	90
SSR-68R	38x15.50R17LT	10	21	13.10	38.20	14.50	17x10-12	65	3640	104
SSR-75R	35x12.50R18LT	8	21	10.60	35.20	12.00	18x8.5-10	50	2910	83
SSR-48R	37x12.50R20LT	10	22	9.96	36.60	12.81	20x10	65	3700	80
SSR-84R	38x15.50R20	8	21	13.10	38.20	13.70	20x10-12	50	3640	101

*(S-Single; D-Dual)

INTERCO TSL / THORNBIRD



The inset shows why the Interco TSL/THORNBIRD is such a Versatile tire. The highway contact area in the illustration shows the tread on hard surfaces. The Three Stage Lugs on the sidewalls do not touch highway surfaces but as soon as the tire gets into mud or snow the sidewall lugs provide decisive traction in forward or reverse. Fiberglass belts under the tread and polyester body plies contribute to a really smooth comfortable ride. The design comes close to being two tires in one... a revolutionary design that has earned its place in the legendary ranks of Super Performance.

Product # B/W	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
T-322/316	29x10.50-15LT	6	22	8.20	28.60	10.80	15x8	45	1495	46/46
T-320/302	30x11.50-15LT	6	22	9.60	29.60	11.90	15x8-10	45	1700	53/53
T- /327	31x11.00-15LT	6	24	8.20	30.80	11.20	15x8	45	2315	58
T-319/309	31x12.50-15LT	6	24	9.80	30.60	13.20	15x10	25	1575	60/61
T-335/325	33x10.50-15LT	6	18	7.75	32.40	11.20	15x8	45	2620	48/52
T- /334	33x11.50-15LT	6	22	8.60	32.20	12.40	15x8-10	45	2715	59
T-314/304	33x12.50-15LT	6	24	9.80	32.30	13.20	15x10	30	2225	68/68
T-340/345	35x12.50-15LT	6	22	10.85	34.50	13.00	15x10	30	2550	76/77
T-317/307	35x14.50-15LT	6	24	11.80	34.30	15.20	15x10	30	2725	89/90
T-347/343	38.5x14.50-15LT	6	19	12.25	37.50	15.20	15x10-12	30	2600	98/99
T-313	30x11.50-16LT	6	22	9.60	30.00	11.90	16x8	45	2050	50
T-330	31x11.00-16LT	6	24	8.20	30.80	11.20	16x8	45	2190	56
T-328/326	LT255/85B16	6	18	7.75	32.70	10.50	16x7	45	2470	53/54
T-329	LT255/85B16	8	18	7.75	32.70	10.50	16x7	60	3000	54
T- /332	33x11.50-16LT	8	22	8.60	32.40	11.70	16x8	45	2630	60
T-341	35x12.50-16LT	8	22	10.85	34.50	12.75	16x10	45	3145	79
T-348/344	38.5x14.50-16LT	6	19	12.04	37.50	14.40	16x10-12	30	2500	97/98
T-333	33x11.50-16.5LT	8	22	12.30	33.00	12.30	16.5x9.75	45	2760	61
T-324	33x12.50-16.5LT	8	24	9.80	32.30	13.20	16.5x9.75	45	2830	68
T-342	35x12.50-16.5LT	8	22	10.85	34.50	12.75	16.5x9.75	45	3360	78
T-318	35x14.50-16.5LT	6	24	11.80	34.30	15.20	16.5x9.75	30	2845	84
T-349	38.5x14.50-16.5LT	6	19	12.25	37.75	15.25	16.5x9.75-12	30	2650	101
T-353	35x12.50-17LT	8	22	10.80	34.80	12.00	17x10	45	3000	
T-354	35x14.50-17LT	8	19	11.80	35.40	14.20	17x12	45	3200	



SUPER SWAMPER TSL / BOGGER

The Super Swamper TSL/BOGGER is built primarily for the professional mud bogger. The tire is versatile... D.O.T. approved and street legal... easy to modify for the cut, open, and pro stock classes. A new design for a new generation of competition performance.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
B-113	31x12.50-15LT	6	25	11.50	30.90	12.50	15x10	30	1750	57
B-126	33x10.50-15LT	6	28	9.80	33.00	11.20	15x7-9	45	3000	58
B-123	33x12.50-15LT	6	23	11.50	33.20	12.80	15x10	30	2205	65
B-107	33x14.00-15LT	6	25	11.50	32.70	13.90	15x10	30	2350	61
B-128	35x10.50-15LT	6	28	9.80	34.80	11.20	15x7-9	45	2600	64
B-115	35x14.50-15LT	6	25	12.50	35.00	14.40	15x10	30	2725	74
B-105	16/35-15LT	6	26	13.75	35.20	15.20	15x12	30	2800	85
B-120	37x13.00-15LT	6	22	12.20	36.80	13.70	15x10	30	2500	84
B-109	38.5x11.00-15LT	6	26	9.25	38.00	12.00	15x8	30	2810	71
B-132	15/38.5-15LT	6	29	12.50	38.40	15.10	15x10-12	45	3000	88
B-103	18/39.5-15LT	6	26	15.00	39.50	16.70	15x12	25	2750	113
B-101	19.5/44 -15LT	6	26	15.30	44.10	18.20	15x12	25	3000	141
B-114	31x12.50-16LT	6	25	11.50	30.90	12.50	16x10	30	1700	55
B-127	33x10.50-16LT	8	28	9.80	33.00	11.02	16x8	60	2975	57
B-124	33x12.50-16LT	6	23	11.50	33.20	12.80	16x10	30	2155	64
B-117	33x14.00-16LT	6	25	11.75	33.10	13.20	16x10	30	2240	62
B-129	35x10.50-16LT	10	28	9.00	34.80	11.12	16x8	75	3400	66
B-118	35x14.50-16LT	6	24	12.50	35.20	14.50	16x10	30	2650	75
B-119	16/35-16LT	6	24	13.75	35.20	14.80	16x12	30	2725	83
B-121	37x13.00-16LT	6	22	12.20	36.80	13.70	16x10	30	2400	83
B-110	38.5x11.00-16LT	6	26	9.25	38.00	11.80	16x8	30	2780	69
B-133	15/38.5-16LT	6	29	12.50	38.40	14.50	16x10-12	45	3000	89
B-135	19.5/44-16LT	6	26	15.30	44.10	18.20	16x12	25	3000	140
B-125	33x12.50-16.5LT	10	20	10.72	33.20	12.50	16.5x9.75	60	3385	67
B-108	33x14.00-16.5LT	6	25	11.50	33.30	13.60	16.5x9.75	30	2400	62
B-116	35x14.50-16.5LT	6	25	12.50	35.00	14.40	16.5x9.75	30	2845	76
B-106	16/35-16.5LT	6	26	13.75	35.20	15.20	16.5x12	30	2750	85
B-112	16/35-16.5LT	10	26	13.75	35.20	15.20	16.5x12	50	3700	88
B-122	37x13.00-16.5LT	6	22	12.00	36.80	13.30	16.5x9.75	30	2450	84
B-130	37x13.00-16.5LT	8	23	12.00	36.80	13.30	16.5x9.75	45	3100	82
B-134	15/38.5-16.5LT	6	29	12.50	38.40	14.50	16.5x9.75-12	45	3000	86
B-111	38.5x11.00-16.5LT	6	26	9.25	38.00	12.00	16.5x8.25	30	3000	70
B-104	18/39.5-16.5LT	6	26	15.00	39.50	16.70	16.5x12	25	2700	116
B-102	19.5/44 -16.5LT	6	26	15.40	44.10	17.90	16.5x12	25	2950	145
B-131	37x13.00-17LT	10	23	12.22	36.80	13.50	17x10	30	4200	84
BOG-5417	19.5/54-17LT	6	COMING SOON							
BOG-5420	19.5/54-20LT	6	27	16.60	53.60	20.62	20x12	25	3640	

TRXUS MUD TERRAIN



TRXUS[®] MT

The NEW TrXus Mud Terrain is INTERCO'S answer to the need of those who want a smooth, super quiet ride with tough thick sidewalls with a chip and cut resistant compound. This tire has more siping than any other mud terrain on the market; which has proven to be almost magical in icy snowy conditions. These same traction features make this tire a serious rock climber.

Each TrXus Mud Terrain tire has its individual specifications and is heavier than the original equipment tires of comparable size. Many brands of tires are made from generic specifications which means there are many brand names coming out of a particular factory but all the tires have a common specification basic body or casing. The only difference is the mold the tire is cured in. The tires will have different tread designs but the body of the tire is common to many others of the same size but under various names.

Product # B/W	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
RXM-05R/052R	31x10.50R15LT	6	19	8.00	31.00	10.80	15x8.5	50	2270	47/47
RXM-06R	33x12.50R15LT	6	19	9.60	33.00	12.70	15x8.5-10	35	2205	58
RXM-09R	34X12.50R15LT	6	19	9.60	34.00	12.90	15x8.5-10	35	2405	64
RXM-11R	35x12.50R15LT	6	19	9.55	34.90	13.00	15x8.5-10	35	2555	66
RXM-30	37x12.50R15LT	6	19	9.25	37.20	13.25	15x10	35	2910	72
RXM-03R	LT235/85R16	10	19	6.90	31.90	9.30	16x6.5	80	*3042S/2778D	51
RXM-04R	LT255/85R16	8	19	7.40	32.70	10.10	16x7	65	*3000S/2755D	53
RXM-01R	LT265/75R16	8	19	7.70	31.90	10.50	16x7.5	65	*3000S/2755D	54
RXM-02R	LT285/75R16	10	19	8.30	32.70	11.20	16x8	80	*3745S/3415D	61
RXM-07R	33x12.50R16LT	10	19	9.60	33.00	12.70	16x8.5-10	65	3195	67
RXM-10R	34x12.50R16LT	10	19	9.60	34.00	12.70	16x8.5-10	65	3415	73
RXM-12R	35x12.50R16LT	10	19	9.55	35.00	12.70	16x8.5-10	65	3640	76
RXM-31	37x12.50R16LT	10	21	9.25	37.20	13.16	16x10	65	3640	79
RXM-34	38.5x14.50R16LT	10	21	10.20	38.60	14.90	16x12	65	4300	
RXM-08R	33x12.50R16.5LT	10	19	9.60	33.00	12.60	16.5x8.25-9.75	65	3525	67
RXM-14R	35x12.50R16.5LT	10	19	9.60	35.00	12.60	16.5x9.75	65	3640	75
RXM-32	37x12.50R16.5LT	10	21	9.25	37.20	13.12	16.5x9.75	65	3970	77
RXM-13R	33x12.50R17LT	10	19	9.60	33.20	12.30	17x8.5-11	65	3085	71
RXM-15R	35x12.50R17LT	10	19	9.60	35.00	12.70	17x8.5-11	65	3640	76
RXM-33	37x12.50R17LT	10	20	9.30	37.20	12.80	17x10	65	3640	78
RXM-35	38.5x14.50R17LT	10	21	10.20	38.60	14.90	17x12	65	4250	85
RXM-25	33x12.50R18LT	10	22	9.40	33.30	13.00	18x10	65	2950	62
RXM-16R	35X12.50R18LT	8	19	9.45	35.15	12.25	18X8.5-10	50	2910	73
RXM-27	35x12.50R18LT	10	21	9.48	35.30	12.40	18x10	65	3445	72
RXM-36	38.5x14.50R18LT	10	21	10.20	38.60	14.90	18x12	65	4200	86
RXM-26	33x12.50R20LT	10	22	9.40	33.40	12.30	20x10	65	2630	62
RXM-28	35x12.50R20LT	10	21	9.30	35.30	12.80	20x10	65	3165	71
RXM-37	38.5x14.50R20LT	10	21	10.20	38.60	14.90	20x12	65	4000	84
RXM-29	35x12.50R22LT	10	21	9.30	35.30	13.40	22x10	65	3000	71

*(S-Single; D-Dual)

RADIAL TRXUS M/T COMPETITION COMPOUND-NON DOT										
MT-RC	37x12.50R17LT	10	21	9.25	37.20	12.77	17x10	65	3640	

TRXUS STS – ALL TERRAIN



TRXUS STS

The TrXus STS, the STS stands for Three Stage Sidewall, is a new concept in all terrain tires. These tires are not intended to be a substitute for the Super Swamper or Bogger tires but a tire for you if you spend a lot of time on the street. Besides working so well on the street it has good off road performance and excels in snow and sand. It is also very much at home in the rocks and will impress anyone with its all around performance. This tire is going to set a new standard in the all terrain category.

BIAS TIRES										
Product # B/W	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
STS- /02	33x13.50-15LT	6	19	10.00	33.00	13.20	15x10	30	2300	55
STS- /16	15/39.5-15LT	6	21	12.00	38.80	16.10	15x10-12	25	2550	92
STS-31/21	21/44-15LT	6	23	15.20	43.60	21.00	15x14	25	3200	139
STS- /04	33x13.50-16LT	8	19	10.00	33.00	12.80	16x10	45	2800	57
STS- /17	15/39.5-16LT	8	21	12.00	39.00	15.50	16x10-12	35	3100	101
STS-32/22	21/44-16LT	8	23	15.20	43.60	21.00	16x14	35	3500	152
STS- /18	15/39.5-16.5LT	8	21	12.00	39.00	16.30	16.5x9.75-12	35	3105	100
STS-33/23	21/44-16.5LT	8	23	15.20	43.60	21.00	16.5x14	35	3525	149
STS- /19	15/39.5-17LT	8	21	12.00	39.00	15.20	17x10-12	35	3050	96
STS-34/24	21/44-17LT	8	23	15.20	43.60	21.00	17x14	35	3300	134
STS-40/20	15/39.5-20LT	8	21	12.00	39.50	14.50	20x10-12	35	3000	91/96
STS-35	21/44-20LT	8	22	15.25	43.75	20.00	20x16	35	3300	139

RADIAL TIRES										
Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
RXS-01R	29x10.50R15LT	6	16	8.80	29.10	10.50	15x7-9	50	1875	42
RXS-02R	31x11.50R15LT	6	16	9.65	31.10	11.85	15x8-10	50	2335	52
RXS-03R	33x12.50R15LT	6	16	10.50	33.10	12.50	15x8.5-10	35	2205	58
RXS-05R	33x14.50R15LT	6	16	12.20	33.30	14.50	15x10-12	35	2365	73
RXS-07R	35x12.50R15LT	6	16	10.50	35.20	13.30	15x8.5-10	35	2555	68
RXS-09R	36x14.50R15LT	6	16	12.20	36.20	14.75	15x10-12	35	2910	82
RXS-12R	38x15.50R15LT	6	16	13.00	38.20	15.50	15x10-12	35	3000	90
RXS-04R	33x12.50R16LT	10	16	10.50	33.10	12.20	16x8.5-10	65	3195	66
RXS-08R	35x12.50R16LT	10	16	10.50	35.10	13.00	16x8.5-10	65	3640	78
RXS-10R	36x14.50R16LT	10	16	12.20	36.10	14.50	16x10-12	65	3640	93
RXS-13R	38x15.50R16LT	10	16	13.00	38.10	15.40	16x10-12	65	3640	101
RXS-11R	36x14.50R16.5LT	10	16	12.20	36.10	14.20	16.5x9.75-12	65	3640	92
RXS-14R	38x15.50R16.5LT	10	16	13.00	38.10	15.40	16.5x9.75-12	65	3640	101
RXS-24	33x12.50R17LT	10	20	11.25	32.50	13.30	17x12	65	3100	66
RXS-19R	35x12.50R17LT	10	16	10.50	35.10	12.80	17x8.5-11	65	3640	76
RXS-15R	38x15.50R17LT	10	16	13.00	38.10	14.80	17x11-13	65	3640	101
RXS-25	33x12.50R18LT	10	20	11.25	32.50	13.30	18x10	65	2950	68
RXS-27	35x12.50R18LT	10	20	11.46	35.20	12.70	18x10	65	3445	
RXS-22	38x15.50R18LT	10	20	12.96	38.10	13.45	18x10	65	4400	98
RXS-26	33x12.50R20LT	10	20	11.25	32.70	12.90	20x10	65	2630	68
RXS-28	35x12.50R20LT	10	20	11.39	35.20	12.70	20x10	65	3165	
RXS-23	38x15.50R20LT	10	20	12.96	38.10	13.40	20x10	65	4200	98
RXS-30	15/39.5R20LT	10	21	11.48	39.10	13.60	20x10	65	4000	97
RXS-29	35x12.50R22LT	10	20	11.37	35.30	12.90	22x10	65	3000	

IROK



IROK

An exciting new “Super Performer”...the **IROK**. Many years of experience have gone into the IROK to develop a tire with traction ‘as good as it gets’ in mud, snow and rock climbing. It has a directional tread in the famous Three Stage Lug design, scooped lugs, blade and molded siping, special sidewall features, extra tough cord and cut resistant compounds in a super traction package.

BIAS TIRES										
Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
I-801	36x13.50-15LT	6	21	11.00	36.80	14.50	15x10	30	2810	66
I-824	37X14.00-15LT	6	21	10.70	36.50	14.71	15x11	30	3085	69
I-808	39.5x13.50-15LT	6	21	11.80	39.50	15.60	15x10	30	3475	76
I-813	14/42-15LT	6	24	11.44	41.50	15.50	15x10	25	3000	95
I-802	36x13.50-16LT	8	21	11.80	36.80	14.20	16x10	45	3460	65
I-825	37X14.00-16LT	8	21	10.71	36.86	14.20	16x11	45	3300	71
I-809	39.5x13.50-16LT	8	21	11.60	39.50	15.00	16x12	45	3640	85
I-814	14/42-16LT	6	24	11.44	41.50	15.40	16x10	25	2950	95
I-803	36x13.50-16.5LT	8	21	11.80	36.80	14.30	16.5x9.75	45	3410	67
I-826	37X14.00-16.5LT	8	21	10.32	36.36	14.25	16.5x11	45	3300	69
I-810	39.5x13.50-16.5LT	8	21	11.60	39.50	15.00	16.5x9.75	45	3640	85
I-815	14/42-16.5LT	6	24	11.44	41.50	15.20	16.5x10.5	25	2950	97
I-823	21/49-16.5LT	6	28	16.50	49.00	20.80	16.5x12	25	3640	169
I-804	36x13.50-17LT	8	21	11.80	36.80	13.80	17x10	45	3360	66
I-827	37X14.00-17LT	8	21	10.62	36.83	13.77	17x11	45	3250	68
I-811	39.5x13.50-17LT	8	21	11.60	39.50	14.50	17x10	45	3640	84
I-816	14/42-17LT	6	24	11.44	41.50	14.80	17x10	25	2900	97
I-821	21/49-17LT	6	28	16.50	49.00	20.80	17x14	25	3640	169
I-805	36x13.50-20LT	8	21	11.00	36.80	12.80	20x10	45	2575	68
I-812	39.5x13.50-20LT	8	21	11.80	39.50	14.50	20x10	45	3600	74
I-822	21/49-20LT	6	28	16.00	49.00	18.80	20x14	25	3640	168

IROK



An exciting new “Super Performer”...the **IROK**. Many years of experience have gone into the IROK to develop a tire with traction ‘as good as it gets’ in mud, snow and rock climbing. It has a directional tread in the famous Three Stage Lug design, scooped lugs, blade and molded siping, special sidewall features, extra tough cord and cut resistant compounds in a super traction package.

RADIAL TIRES

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
ROK-01	36x13.50R15LT	6	21	11.00	36.00	13.50	15x10	65	2810	81
ROK-20	37x12.50R15LT	6	21	10.50	36.90	13.40	15x8.5-11	35	2910	77
ROK-06	39.5x13.50R15LT	6	21	11.00	39.50	13.75	15x10	35	3475	96
ROK-02	36x13.50R16LT	10	21	11.00	36.00	13.00	16x10	65	3800	85
ROK-21	37x12.50R16LT	10	21	10.50	36.90	13.30	16x8.5-11	65	3640	89
ROK-07	39.5x13.50R16LT	10	21	11.00	39.50	13.75	16x10	65	4080	96
ROK-27	41x14.50R16LT	8	20	11.50	41.00	14.20	16x12	50	3850	
ROK-03	36x13.50R16.5LT	10	21	11.00	36.00	13.00	16.5x9.75	65	3700	86
ROK-22	37x12.50R16.5LT	10	21	10.50	36.90	13.30	16.5x8.25	65	3970	89
ROK-08	39.5x13.50R16.5LT	10	21	11.00	39.50	13.75	16.5x9.75	65	4080	97
ROK-11	33x13.50R17LT	8	21	11.50	33.00	13.00	17x10	50	2675	68
ROK-14	35x14.50R17LT	8	21	12.72	35.00	13.20	17x10	50	3195	78
ROK-04	36x13.50R17LT	10	21	11.00	36.00	13.50	17x10	65	3600	84
ROK-23	37x12.50R17LT	10	21	10.50	36.90	13.10	17x8.5-11	65	3640	90
ROK-09	39.5x13.50R17LT	10	21	11.00	39.50	13.25	17x10	65	4080	99
ROK-28	41x14.50R17LT	8	20	11.50	41.00	14.20	17x12	50	3850	
ROK-12	33x13.50R18LT	10	21	10.50	33.00	12.80	18x10	50	2560	65
ROK-15	35x14.50R18LT	8	21	12.72	35.05	12.80	18x10	50	3100	77
ROK-24	41x14.50R18	8	19	12.00	40.84	13.92	18x10-12	50	3750	98
ROK-13	33x13.50R20LT	8	21	11.50	33.00	12.40	20x10	50	2510	64
ROK-16	35x14.50R20LT	8	21	12.72	35.15	12.80	20x10	50	2825	76
ROK-05	36x13.50R20LT	10	21	11.00	36.00	12.50	20x10	65	3200	74
ROK-10	39.5x13.50R20LT	10	21	11.00	39.50	12.75	20x10	65	4080	87
ROK-25	41x14.35R20	8	19	12.44	40.97	14.97	20x12	50	3750	99
ROK-17	35x14.50R22LT	8	21	12.20	35.08	13.30	22x12	50	2500	
ROK-26	41x14.50R22	8	20	12.75	40.97	13.92	22x12	50	3500	

GROUND HAWG



GROUND HAWG



The Ground Hawk is a great directional tire with superior performance in mud and deep snow, and performs well on the street. The aggressive tread wears well under normal highway usage and is available in both a bias ply and radial construction.

BIAS TIRES

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
RV-07	12-15LT	6	21	10.00	33.00	12.30	15x10	30	2250	59
RV-11	14/35-15LT	6	24	10.00	34.50	13.40	15x10	45	2850	71
RV-36	15/38.5-15LT	6	24	10.00	38.00	14.50	15x10	45	3000	74
RV-39	17/40-15LT	6	24	14.00	39.00	15.50	15x10	30	2685	100
RV-44	18.5/44-15LT	6	24	14.00	43.80	17.80	15x12	30	2855	121
RV-14	12-16.5LT	8	21	10.00	33.00	12.0	16.5x9.75	45	3000	56
RV-15	14/35-16.5LT	6	24	10.00	34.50	12.7	16.5x9.75	45	2850	67
RV-37	15/38.5-16.5LT	6	24	11.00	38.00	37.7	16.5x9.75	45	3000	75
RV-40	17/40-16.5LT	6	24	14.00	39.00	14.7	16.5x9.75	30	2685	99
RV-45	18.5/44-16.5LT	6	24	14.00	43.80	17.8	16.5x12	30	2855	120
RV-35	15/38.5-17 LT	6	24	11.00	38.00	14.0	17x10-12	45	3000	79
RV-08	17/40-17LT	6	24	14.00	39.00	15.40	17x12-14	30	2685	

RADIAL TIRES

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
RV-51R	32x11.50R15LT	6	20	9.20	32.00	11.60	8x15	50	2530	53
RV-52R	36x14.50R15LT	6	21	10.40	36.00	14.30	10x15	35	2910	76
RV-55R	38x15.50R15LT	6	20	10.70	37.20	15.20	12x15	35	3010	86
RV-62R	32x11.50R16LT	10	20	9.20	32.00	10.56	16x8-10	80	3305	
RV-58R	36x14.50R16LT	10	21	10.30	35.80	14.30	16x10-12	65	3640	81
RV-57R	38x15.50R16LT	10	21	10.30	37.56	14.60	16x10-12	65	3640	90
RV-60R	36x14.50R16.5LT	10	21	10.40	36.00	13.50	9.75x16.5	65	3640	86
RV-61R	38x15.50R16.5LT	10	20	10.70	37.20	14.40	12x16.5	65	3640	97

VAMPIRE TSL



No Tires Out Perform the Vampires . . . Believe It!



The Super Swamper TSL/Vampire is the big brother to the Super Swamper TSL/ATV tire...the Vampire steps away from all other ATV tires. The Super Swamper TSL/Vampire is as rugged as they come. The Vampires are 30% to 35% heavier than the regular Super Swamper. The deep lugs give longer tread life with the 43/32nds of tread depth and unsurpassed forward, reverse and lateral traction. The Vampires are so strong they continue to run under most load conditions even when punctured. As long as the Vampire does not become unseated from the rim the tire will almost always get you back... even without air.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
VAM-01	22x12.50-9	4	41	10.51	21.75	11.70	9x9	5	385 #'s@	24
VAM-02	22x12.50-10	4	41	10.51	21.75	10.70	10x8	5	375 #'s@	25
VAM-33	24x9.00-10	4	43	8.10	24.00	9.00	10x7	5	305 #'s @	20
VAM-24	24x9.00-11	4	43	8.10	24.00	9.00	11x7	5	310 #'s @	21
VAM-21	25x9.50-10	4	43	8.10	25.00	9.50	10x7	5	365 #'s @	22
VAM-22	25x9.50-11	4	43	8.10	24.70	9.50	11x7	5	355 #'s @	22
VAM-23	25x9.50-12	4	43	8.10	25.00	9.00	12x7	5	355 #'s @	23
VAM-17	25x13.00-9	4	43	9.75	25.20	12.20	9x7	5	470 #'s @	31
VAM-18	25x13.00-10	4	43	9.75	25.20	12.20	10x7	5	470 #'s @	33
VAM-19	25x12.00-11	4	43	9.75	25.20	12.20	11x7	5	460 #'s @	31
VAM-20	25x12.00-12	4	43	11.30	25.30	11.70	12x7	5	430 #'s @	30
VAM-25	25x9.50-10	4	43	8.00	26.00	9.30	10x7	5	370 #'s @	23
VAM-26	25x9.50-11	4	43	8.20	26.20	9.30	11x7	5	370 #'s @	23
VAM-27	26x9.50-12	4	43	8.40	25.80	9.10	12x7	5	345 #'s @	24
VAM-30	26x12.00-10	4	43	12.20	26.20	12.00	10x7	5	470 #'s @	23
VAM-31	26x12.00-11	4	43	12.20	26.20	12.00	11x7	5	470 #'s @	31
VAM-32	26x12.00-12	4	43	12.20	26.20	12.00	12x7	5	460 #'s @	35
VAM-34	27x10.00-10	4	44	7.50	26.80	9.00	10x7	5	370 #'s @	25
VAM-35	27x10.00-11	4	44	7.50	26.80	9.00	11x7	5	390 #'s @	24
VAM-36	27x10.00-12	4	44	7.50	26.80	9.00	12x7	5	400 #'s @	25
VAM-37	27x12.00-11	4	39	12.00	27.00	10.75	11x7	5	480 #'s @	32
VAM-38	27x12.00-12	4	39	12.00	27.00	12.20	12x7	5	480 #'s @	35

VAMPIRE ASX



No Tires Out Perform the Vampires . . . Believe It!



The Vampire ASX is the only Asymmetrical ATV tire in the world. The outside sidewall has a full sidewall tread on one side (asymmetrical). This gives the tire excellent characteristics for climbing out of ruts, excellent rim and sidewall protection, and allows for an increase in tire width without the problems of rubbing on the frame. When purchasing these tires remember you will need two for the left and two for the right side of the ATV.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
ASX-01	26x9.50 - 12	4	26	9.20	26.00	9.50	12x7	5	380 #'s @	27
ASX-02	26x9.50 - 12	4	26	9.20	26.00	9.50	12x7	5	380#'s @	27
ASX-03	26x13.00 - 12	4	32	13.40	26.00	13.80	12x10	5	455 #'s @	36
ASX-04	26x13.00 - 12	4	32	13.40	26.00	13.80	12x10	5	455#'s @	36

VAMPIRE EDL



No Tires Out Perform the Vampires . . . Believe It!



The Vampire EDL (Extra Deep Lug) has the deepest lug of any of the ATV tires on the market. It is designed for the larger ATV's that have the clearance and power to take advantage of the unsurpassed traction built into this tire.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
VAM-39	28x10.00 - 12	4	64	8.50	28.20	8.70	12x7	5	390 #'s @	40

SUPER SWAMPER TSL / ATV



The Super Swamper TSL /ATV is the ATV tire designed with absolute performance in mind. A combination of hot performance in slushy conditions while giving excellent grip on packed terrain and a smooth ride as well. The lateral traction of the Super Swamper TSL/ATV has been reduced to allow the tire to skid sideways which decreases the chances of rollover in tight turns. This is the tire that opened up a whole new world to the ATV enthusiast.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
ATV-01	22x9.0-10	4	26	8.50	22.30	9.00	10x7	5	265#s@	18
ATV-02	22x12.5-8	4	26	10.80	21.60	12.60	8x7	5	395#s@	20
ATV-03	22x12.5-9	4	26	10.80	21.80	12.30	9x8-10	5	385#s@	19
ATV-04	22x12.5-10	4	26	10.80	21.80	12.30	10x8-10	5	385#s@	19
ATV-11	24x9.0-10	4	26	8.90	24.20	9.30	10x7-8	5	310#s@	22
ATV-12	24x9.0-11	4	26	8.90	24.30	9.20	11x7	5	310#s@	22
ATV-05	25x9.5-10	4	26	9.00	24.90	9.40	10x7	5	365#s@	20
ATV-06	25x9.5-11	4	26	9.00	25.10	9.20	11x7	5	355#s@	20
ATV-07	25x9.5-12	4	26	9.00	25.00	9.20	12x7	5	355#s@	21
ATV-09	25x13.5-9	4	26	11.50	25.00	13.10	9x7	5	495#s@	25
ATV-10	25x13.5-10	4	26	11.50	25.00	13.10	10x7	5	495#s@	25
ATV-13	25x12.5-11	4	26	11.50	25.50	12.50	11x7	5	440#s@	24
ATV-14	25x12.5-12	4	26	11.60	25.50	12.00	12x7	5	430#s@	26
ATV-15	26x9.5-11	4	32	9.30	25.90	11.50	11x7	5	375#s@	21
ATV-16	26x9.5-12	4	32	9.30	26.00	9.50	12x7	5	375#s@	21
ATV-17	26x12.0-12	4	32	11.70	26.00	12.00	12x7	5	455#s@	27
ATV-18	26x9.0-10	4	32	8.80	26.90	9.50	10x7	5	385#s@	25
ATV-19	27x9.0-11	4	32	8.80	26.90	9.40	11x7	5	375#s@	28
ATV-20	27x9.0-12	4	30	8.80	26.90	9.10	12x7	5	365#s@	29
ATV-21	27x12.0-10	4	32	11.70	23.90	12.70	10x7	5	480#s@	30
ATV-22	27x12.0-11	4	32	11.70	27.20	12.50	11x7	5	480#s@	29
ATV-23	27x12.0-12	4	32	11.30	27.40	12.50	12x7	5	480#s@	34

SWAMP LITE



Continuing the tradition of performance the SwampLite ATV tire in 6-ply rating cuts a new standard of excellence in mud, snow, and hardpack. Distinctly designed with all features contributing to excellent versatile performance and lighter ground disturbance than many tires with lesser capabilities.

Product #	Size	Ply	TD	TW	O.D.	C.S.	Rim	Max. Infla.	Max. Load	Wt
SWL-54	22x11.00-9	6								
SWL-59	22x7.00-11	6								
SWL-55	25x12.00-9	6								
SWL-52	22x8.00-10	6								
SWL-57	23x8.00-10	6								
SWL-56	22x11.00-10	6								
SWL-58	25x11.00-10	6								
SWL-60	25x8.00-11	6								
SWL-62	25x10.00-11	6								
SWL-64	25x8.00-12	6								
SWL-66	25x10.00-12	6								
SWL-68	26x10.00-12	6								
SWL-70	26x12.00-12	6								
SWL-72	27x10.00-12	6								
SWL-74	27x12.00-12	6								
SWL-76	28x10.00-12	6								
SWL-78	29.5x10.00-12	6								
SWL-79	27x9.00-14	6								
SWL-80	27x11.00-14	6								