



## OFF THE ROAD TIRES

### L2/GE AMERICAN CONTRACTOR® LOADER/GRADER



FIG A



FIG B



FIG C

These high-quality tubeless tires are designed for rad graders, front end loaders, dozers, forlift trucks and scapers are used extensively by general contractors, highway and building crews, the construction industry and many other heavy-duty users.

G2 / L2 American Contractor® Loader/Grader

SIZE	FIG	PLY RATING	PRODUCT CODE	DESC	TREAD DEPTH	OVERALL DIA	RIM WIDTH	OVERALL WIDTH	MAX	MAX LOAD 25	WEIGHT
									INFLATION		
8.25-20TG	B	6	DEAPB	G2	23/32	38.2	6.5	9.8	30	2260	66
13.00-24TG	A	12	NC5C7	G2	28/32	50.8	8	13.1	44	6000	136
13.00-24TG	A	16	NC5CB	G2	28/32	50.8	8	13.1	54	6760	150
14.00-24TG	A	12	NC5A7	G2/L2	34/32	53.1	8	14.25	36	6800	156
14.00-24TG	A	16	NC5AB	G2/L2	34/32	53.1	8	14.25	51	8050	171
16.00-24TG	A	12	NC5N7	E2/G2/L2	36/32	59.2	10	16.8	33	8050	250
16.00-24TG	A	16	NC5NB	E2/G2/L2	36/32	59.2	10	16.8	44	9900	271
15.5-25	A	12	NC5M7	E2/G2/L2	28/32	51	12	15.5	36	2650	147
15.5-25	A	16	NC5MB	E2/G2/L2	28/32	51	12	15.5	47	3100	163
17.5-25	A	12	NC5B7	E2/G2/L2	32/32	53.5	14	17.5	29	6400	184
17.5-25	A	16	NC5BB	E2/G2/L2	32/32	53.5	14	17.5	40	7400	190
17.5-25	A	20	NC5BF	E2/G2/L2	32/32	52.3	14	17.5	47	8050	207
18.00-25	C	12	NC5AC	E2/G2/L2	40/32	63.5	13	19	29	10500	371
18.00-25	C	16	NC5AD	E2/G2/L2	40/32	63.5	13	19	40	12300	409
20.5-25	A	12	NC5D7	E2/G2/L2	36/32	58.6	17	20.5	25	7850	246
20.5-25	A	16	NC5DB	E2/G2/L2	36/32	58.6	17	20.5	33	8800	266
20.5-25	A	20	NC5DF	E2/G2/L2	36/32	58.6	17	20.5	40	9900	287
23.5-25	C	12	NC557	E2/G2/L2	40/32	63.68	19.5	23.5	29	10500	410
23.5-25	C	16	NC55B	E2/G2/L2	40/32	63.68	19.5	23.5	36	12000	428



## E3/L3 - E4/L4 AMERICAN CONTRACTOR® ROCK SERVICE



FIG B



FIG C

Built with heavy-duty carcass and a special compound for a cut resistant tread, these tires offer unparalleled protection on sharp rocks in quarry uses. A deeper tread allows for superior traction in off road environments.

AMERICAN CONTRACTOR - STA E3/L3, E4/L4 ROCK SERVICE											
SIZE	FIG	PLY RATING	PRODUCT	DESCRIPTI ON	TREAD	OVERALL	RIM	OVERALL	MAX	MAX	WT
			CODE		DEPTH	DIAMETER	WIDTH	WIDTH	INFLATION	LOAD	
16.00-25		28	NC2VP	E4/L4 TB	54/32	58.7	11.25	18.7	83(E4)	14800(E4)	521
12.00-24	B	20	NA3PE	E3/L3 TT	28/32	48.1	8.5	12.5	80 (E3) 120 (L3)	8050 (E3) 15210 (L3)	195
14.00-24	B	20	NA3TE	E3/L3 TT	30/32	53.4	10	14.7	69 (E3) 102 (L3)	10200 (E3) 18700 (L3)	269
14.00-24	B	24	NA3TK	E3/L3 TT	30/32	53.4	10	14.7	83 (E3) 116 (L3)	11400 (E3) 20390 (L3)	274
16.00-24	C	16	NA3NB	E3/L3 TL	34/32	59	10	16.5	45 (E3) 62 (L3)	10400 (E3) 18200 (L3)	339
16.00-24	C	20	NA3NF	E3/L3 TL	34/32	59	10	16.5	60 (E3) 77 (L3)	12300 (E3) 14250 (L3)	362
15.5-25	C	12	NA3M7	E3/L3 TL	32/32	50.5	12	15.5	36 (E3) 58 (L3)	7150 (E3) 12300 (L3)	176
15.5-25	C	16	NA3MB	E3/L3 TL	32/32	50.5	12	15.5	47 (E3) 76 (L3)	8350 (E3) 14400 (L3)	192



SIZE	FIG	PLY RATING	PRODUCT	DESCRIP	TREAD	OVERALL	RIM	OVERALL	MAX	MAX	WT
			CODE		DEPTH	DIAMETER	WIDTH	WIDTH	INFLATION	LOAD	
16.00-25	C	24	NA3VL	E3/L3 TL	32/32	59	11.25	16.5	69 (E3) 94 (L3)	8350 (E3) 14400 (L3)	394
16.00-25	C	28	NA3VP	E3/L3 TL	32/32	59	11.25	16.5	47 (E3) 76 (L3)	13200 (E3) 23400 (L3)	420
17.5-25	C	12	NA3B7	E3/L3 TL	32/32	53.2	14	17.8	83 (E3) 109 (L3)	8050 (E3) 14800 (L3)	228
17.5-25	C	16	NA3BB	E3/L3 TL	32/32	53.2	14	17.8	44 (E3) 69 (L3)	25400 (E3) 16100 (L3)	251
20.5-25	C	16	NA3DB	E3/L3 TL	38/32	59.2	17	20.2	40 (E3) 51 (L3)	12000 (E3) 18200 (L3)	342
20.5-25	C	20	NA3DF	E3/L3 TL	38/32	59.2	17	20.2	47 (E3) 65 (L3)	13200 (E3) 20900 (L3)	365
23.5-25	C	16	NA35B	E3/L3 TL	40/32	63.7	19.5	23.5	33 (E3) 44 (L3)	13600 (E3) 20900 (L3)	483
23.5-25	C	20	NA35F	E3/L3 TL	40/32	63.7	19.5	23.5	44 (E3) 54 (L3)	16100 (E3) 24000 (L3)	507
26.5-25	C	20	NA3UF	E3/L3 TL	44/32	69	22	26.8	36 (E3) 51 (L3)	18200 (E3) 29100 (L3)	752
26.5-25		20	NC1UF	XT3 E/L3	48/32	68	22	27.2	36 (E3) (L3)	18200 (E3) (L3)	800
26.5-25	C	26	NA3UN	E3/L3 TL	44/32	69	22	26.8	51 (E3) 69 (L3)	22000 (E3) 34200 (L3)	783
26.5-25		28	NC1UN	XT3 E/L3	48/32	68	22	27.2	51(E3) (L3)	22000 (E3) (L3)	825
29.5-25	C	22	NA39J	E3/L3 TL	45/32	73.2	25	30.5	36 (E3) 47 (L3)	22000 (E3) 33100 (L3)	911
29.5-25	C	28	NA39P	E3/L3 TL	45/32	73.2	25	30.5	47 (E3) 62 (L3)	26800 (E3) 41900 (L3)	943



## R4 AMERICAN CONTRACTOR® INDUSTRIAL TRACTOR



FIG C



FIG D

These versatile tires are specially constructed with a heavier carcass and tougher compounds for severe applications and used on back hoes, snow removal equipment and a wide variety of industrial applications.

### AMERICAN CONTRACTOR - R4 - INDUSTRIAL TRACTOR

SIZE	FIG	PLY	PRODUCT	DESCRIP	TREAD	OVERALL	RIM	OVERALL	MAX	MAX	WEIGHT
		RATING	CODE		DEPTH	DIA	WIDTH	WIDTH	INFLATION	LOAD	
											25 MPH
14.9-24	C	8	NC5E3	R4	33/32	48.6	13	14.9	30	5080	119
16.9-24	C	8	NC5F3	R4	35/32	51.5	15	16.9	28	5840	148
17.5L-24	C	8	NC5H3	R4	33/32	49.2	15	17.5	26	5360	139
17.5L-24	C	12	NC5H5	R4	33/32	49.2	15	17.5	34	4680	151
18.4-24	C	10	NC5J5	R4	36/32	54.2	16	18.4	30	7400	176
19.5L-24	C	10	NC5K5	R4	34/32	51.5	17	19.5	28	6600	186
19.5L-24	C	12	NC5K7	R4	34/32	51.5	17	19.5	34	7600	191
21L-24	C	12	NC5L7	R4	35/32	54.5	18	21	32	8550	236
16.9-28	D	10	NC575	R4	31/32	56.5	15	18.1	32	6800	172
16.9-28	D	12	NC577	R4	31/32	56.5	15	18.1	38	7550	174

## AMERICAN LOGGER® TIRES



FIG B



FIG C

These high quality settl belted tires are designed for forestsy applications and feature advanced rubber compounds that provide the maximum resistance to cutting, chipping and punctures.

### AMERICAN LOGGER

SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	DESCRIP	TREAD DEPTH	OVERALL DIA	RIM WIDTH	MAX	MAX LOAD	WEIGHT
								INFLATIO N		
23.1-26	B	10	NF146	LS2	67/32	64.8	20	25	10000	573
23.1-26	B	16	NF14C	LS2	67/32	64.8	20	40	13750	600
28L-26	B	12	NF168	LS2	72/32	64.72	25	25	11600	658
28L-26	B	14	NF16A	LS2	72/32	64.72	25	30	13100	658
28L-26	B	16	NF16C	LS2	72/32	64.72	25	35	14325	658
24.5-32	B	16	NF18C	LS2	68/32	72	21	35	15400	639
30.5L-32	B	16	NF1CB	LS2	70/32	72.5	27	30	16400	788
30.5L-32	B	20	NF1AA	LS2	70/32	72.5	27	35	17950	821
18.4-34	B	10	NF1N6	LS2	64/32	66.8	16	30	8950	414
18.4-26	C	10	NF2A6	LS1	51/32	58.8	16	30	7950	264



## L5 BIG JAKE®

Big Jake® tires are specifically compounded to perform under severe conditions for heavy-duty applications. The durability, extremely deep tread depth and resistance to hot droplets make these ideal for mining and steel or aluminum mill applications



### L5S

SIZE	PLY RATING	PRODUCT CODE	DESCRIPT	TREAD DEPTH	OVERALL DIA	RIM WIDTH	OVERALL WIDTH	MAX INFLATION	MAX LOAD 5MPH	WEIGHT
9.50-20	14	NDA1A	L5 S	32/32	41.2	7	10.97	75	8050	142
10.00-20	14	NDA2A	L5 S	32/32	41.2	7.5	10.99	75	9100	149
14.00-24	20	NDATE	L5 S	67/32	55.8	10	14.8	102	18700	523
14.00-24	28	NDATL	L5 S	67/32	55.8	10	14.8	141	22700	539
12.00-24	16	NDAPC	L5 S	86/32	50.5	8.5	12.4	98	13600	326
12.00-24	20	NDAPE	L5 S	86/32	50.5	8.5	12.4	120*	15210	341
17.50-25	20	NDABF	L5 S	86/32	55.1	14	17.5	83	18200	526
18.00-25	24	NDAAT	L5 S	99/32	64.5	13	21.5	80	27600	920
18.00-25	32	NDALT	L5 S	99/32	64.5	13	21.5	109	33100	1031
18.00-25	40	NDALW	L5 S	99/32	64.5	13	21.5	138	37500	1058
23.50-25	20	NDA5B	L5 S	99/32	65.8	19.5	24.5	54	24000	1109
26.50-25	26	NDAUN	L5 S	110/32	70	22	28.7	65	33100	1448
26.50-25	32	NDAUP	L5 S	110/32	70	22	28.7	80	37500	1542
29.50-25	28	NDA9P	L5 S	110/32	71.7	22	29.5	62	38600	1669
29.50-25	34	NDA9T	L5 S	110/32	71.7	25	29.5	76	44100	1711

Please look below for Big Jake® L5 product specifications:

### L5

SIZE	PLY RATING	PRODUCT CODE	DESCRIPT	TREAD DEPTH	OVERALL DIA	RIM WIDTH	OVERALL WIDTH	MAX INFLATION	MAX LOAD 5MPH	WEIGHT
26.50-25	20	NDCUF	L5 TB	110/32	69.7	22	25.7	51	29100	1328
26.50-25	26	NDCUN	L5 TB	110/32	69.7	22	25.7	65	33100	1365
26.50-25	32	NDCUP	L5 TB	110/32	69.7	22	25.7	80	37500	1428
29.50-25	28	NDC9P	L5 TB	110/32	72	25	29.2	62	38600	1684



## L4/L5 AMERICAN CARRIER



These extra heavy duty tires are designed for large container handlers, reach stackers and forklifts used in the demanding environment of ports, rail terminals and container yards and offer superior traction.

**L4/L5 AMERICAN CARRIER**

SIZE	PLY RATING	PRODUCT CODE	DESCRIPT	TREAD DEPTH	OVERALL DIA	RIM WIDTH	OVERALL WIDTH	MAX INFLATION	MAX	WEIGHT
									LOAD	
									5 MPH	
18.00-25	32	NE1LT	L4S	72/32	63.7	13	18	80	18810	872
18.00-25	40	NE1LW	L4S	72/32	63.7	13	18	80	37500	935
18.00-25	40	NC2LW	L4	68/32	64.5	13	22.8	138	37500	793
18.00-25	40	NA1LW	L5S	99/32	64.5	13	21.5	138	37480	1074



## MATERIAL HANDLING

### SUPER LUG® - HEAVY DUTY - INDUSTRIAL HANDLING EQUIPMENT

Heavy-duty tire for forklifts, industrial vehicles, dock handling equipment, material handling and scrapers.



**SUPER LUG HEAVY DUTY**

SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
*18X7-8 NHS	8	DP2A5	18/32	6.6	18	4.33	20
18X7-8 NHS	12	DP2A6	18/32	6.6	18	4.33	21
18X7-8 NHS	16	DP2A7	18/32	6.6	18	4.33	23
*18X8-8 NHS	14	DP2AD	18/32	8.1	18	5.5	24
18X9-8 NHS	16	DP2AA	18/32	9.1	18.1	7	27
6.90-9 NHS	10	DP2B3	19/32	6.3	21.4	5.5	23
21X8-9 NHS	12	DP2BD	19/32	8.2	21.1	6	28
21X9-9 NHS	12	DP2B8	19/32	9	21.1	7	30
6.50-10 NHS	10	DP2C3	20/32	7	23.4	5	27
6.50-10 NHS	12	DP2L4	20/32	7	23.4	5	27
*7.50-10 NHS	14	DP2DE	25/32	8.2	25	5.5	53
7.50-10 NHS	16	DP2FC	25/32	8.2	25	5.5	53
21X8-10 NHS	14	DP2CM	32/32	8.1	20.8	6.5	45
23X8-10 NHS	10	DP2CL	20/32	7.8	23.4	6.5	31
23X9-10 NHS	16	DP2BF	20/32	8.3	23.4	6.5	40
27X9-10 NHS	16	DP2DD	25/32	9.5	26.7	6.5	73
27X15-10 NHS	20	DP2AP	34/32	14.5	27.7	14.5	164
7.00-12 NHS	12	DP2D1	30/32	7.2	26.6	7.2	50
23X10-12 NHS	14	DP2AL	25/32	10.1	23	10.1	51
23X10-12 NHS	18	DP2AN	25/32	10.1	23	10.1	63
24X12-12 NHS	24	DP2M9	25/32	11.5	23.5	11.5	76
27X10-12 NHS	12	DP2AJ	30/32	9.8	27	9.8	46
250-15 NHS	20	DP2BH	30/32	9.5	28.7	7.5	88
29X8-15 NHS	12	DP2E4	30/32	7.8	28.7	5.5	62
7.50-15 NHS "32"	12	DP2EA	29/32	8.6	32	6	76
*7.50-15 NHS "32"	16	DP2D6	29/32	8.6	32	6	90
*8.25-15 NHS	12	DP2ED	25/32	9.4	33.3	6.5	92
8.25-15 NHS	16	DP2FD	25/32	9.4	33.3	6.5	102
27X12-15 NHS	16	DP2K5	29/32	12	26.8	10	88
*27X15-15 NHS	24	DP2J5	29/32	15	26.8	13	114
28X9-15 NHS	12	DP2EW	29/32	9	28	7	74
28X12-15 NHS	20	DP2K3	29/32	12	28	9.75	98



## SUPER LUG® - HEAVY DUTY - INDUSTRIAL HANDLING EQUIPMENT

### ADDITIONAL SUPER LUG TIRES

SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
28X13-15 NHS	20	DP2JA	29/32	13	28	11.5	103
28X13-15 NHS	28	DP2JC	29/32	13	28	11.5	105
*28X15-15 NHS	24	DP2JD	29/32	15	28	13	120
*32X10.5-15 NHS	20	DP2JE	28/32	10.4	32.1	8	113
32X12.5-15 NHS	20	DP2JH	28/32	12.3	32.5	10	133
33X11-15 NHS	20	DP2K1	25/32	11	33.7	8	110
*36X11-15 NHS	14	DP2FT	34/32	10.9	36	7.5	137
*36X11-15 NHS	16	DP2EL	34/32	10.9	36	7.5	146
36X11-15 NHS	22	DP2FX	34/32	10.9	36	7.5	154
35X15-15 NHS	16	DP2EN	33/32	14.6	35.4	10.5	179
35X15-15 NHS	24	DP2HP	33/32	14.6	35.4	10.5	207
35X15-15 NHS	32	DP2K8	33/32	14.6	35.4	10.5	218
8.25-20 NHS	12	DP2H2	32/32	9.7	39	6.5	126
*10.00-20 NHS	14	DP2H6	32/32	11.5	42.9	7.5	167
10.00-20 NHS	16	DP2H7	32/32	11.5	42.9	7.5	172
12.00-20 NHS	16	DP2H8	34/32	12.4	45	8.5	211
*12.00-20 NHS	24	DP2HH	34/32	12.4	45	8.5	240
39X11.5-20 NHS	20	DP2D7	31/32	10.6	39.3	8	161
44X18-20 NHS	24	DP2HL	33/32	18	44.2	15	297
44X18-20 NHS	32	DP2HY	33/32	18	44.2	15	317
12.00-24 NHS	20	DF8BM	30/32	13	49.6	8.5	204
12.00-24 NHS	24	DF8HW	30/32	13	49.6	8.5	206

### INDUSTRIAL DEEP LUG®

Lug design for industrial vehicles and counter balanced forklifts, lighter than the Superlug®, with more aggressive traction.



### INDUSTRIAL DEEP LUG

SIZE	PLY RATING	PRODUCT CODE	TREAD	SECTION	OVERALL DIAMETER	RIM	WEIGHT
			DEPTH	WIDTH		WIDTH	
5.70-8 NHS	8	DF9A4	17/32	5.7	18.5	4.5	13
*5.70-8 NHS	10	DF9AV	17/32	5.7	18.5	4.5	14
*6.90-9 NHS	6	DF9B1	19/32	6.5	21.5	5.5	21
6.90-9 NHS	10	DF9B3	19/32	6.5	21.5	5.5	20
6.90-9 NHS	12	DF9BE	19/32	6.5	21.5	5	22
6.50-10 NHS	10	DF9C3	20/32	7	23.6	5.5	25
7.50-10 NHS	10	DF9C5	21/32	7.9	25.5	5.5	31
7.50-10 NHS	12	DF9C6	21/32	7.9	25.5	5.5	35
*7.50-10 NHS	16	DF9DF	21/32	7.9	25.5	5.5	44
7.00-12 NHS	12	DF9D1	20/32	7.4	27	5	36
*7.00L-15 NHS	10	DF9DX	20/32	7.3	29.1	5.5	38
7.00L-15 NHS	12	DF9E4	20/32	7.3	29.1	5.5	43
*7.50-15 NHS	10	DF9E7	21/32	7.6	30.6	6	48
7.50-15 NHS	12	DF9E8	21/32	7.6	30.6	6	48
*7.50-15 NHS	10	DF9E9	20/32	8.1	31.7	6	51
7.50-15 NHS	12	DF9EA	20/32	8.1	31.7	6	52
28X9-15 NHS	12	DF9EC	20/32	8.6	27.3	7	41
*8.25-15 NHS	8	DF9BM	21/32	9.3	33.2	6.5	57
8.25-15 NHS	12	DF9EE	21/32	9.3	33.2	6.5	63



## SKID STEER - BIG JAKE ® - STA LOADER



BIG JAKE SKID STEER							
SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	WEIGHT
10-16.5NHS *	6	DB3D4	32/32	10.66	30.59	7.25	66
10-16.5NHS *	8	DB3DM	32/32	10.66	30.59	7.25	67
10-16.5NHS +	10	DB3DN	32/32	10.66	30.59	7.25	69
10-16.5 NHS	10	TBA	26/32				
12-16.5 NHS	12	TBA	29/32				
33/15.5-16.5 NHS	12	DHDF8	29/32	14.46	32.9	9.75	91

+ Steel Belted available

\* Non Stocking items

## AMERICAN COMPACTOR C-1

Used on construction equipment, compacting dirt, paving equipment and soil compaction. Improves smoothness on uneven surfaces - tracks, tractor pulls.



AMERICAN COMPACTOR C-1							
SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
7.50-15	6	DECD8	11/32	9.4	30.5	6	37
7.50-15	12	DECE3	11/32	9.4	30.5	6	46
9.00-20	16	DHCB9	16/32	10.75	39.6	7	103
11.00-20	16	DHCFE	16/32	11.6	41.61	8	151
13.00-24	14	DHCC8	64/32	11.9	49.8	10	206



## STA TRAXION® - STA LOADER



A

B

C

D

STA Traxion® and STA loader Industrial handling tires are specifically designed for use on Ditch Witch, trenchers, Moffit, materials handling and sod rolling.

### STA TRAXION

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
26X12-12 NHS	A	4	DE1DM	23/32	12	25.8	10.5	27
26X12-12 NHS	A	8	DE1DP	23/32	12	25.8	10.5	31
26X12-12 NHS	A	12	DE1DT	23/32	12	25.8	10.5	33
31X15.50-15 NHS	A	8	DJ1F4	23/32	14.7	31	13	58
31X15.50-15 NHS	A	12	DJ1M6	23/32	14.7	31	13	60
33X12.50-15 NHS	C	8	DE1M3	21/32	13	32.6	10	51

### LOADER

27X8.50-15 NHS	D	4	DP7FR	16/32	8.1	26.7	7	28
27X8.50-15 NHS	D	6	DP7MB	16/32	8.1	26.7	7	30
27X10.50-15 NHS	D	6	DP7MR	16/32	10	27	8	36
10-16.5 NHS	D	6	DP7D4	20/32	10	30.4	8.25	41
*10-16.5 NHS	D	6	DP8D4	20/32	10	30.4	8.25	46
10-16.5 NHS	D	8	DP7DM	20/32	10	30.4	8.25	42
10-16.5 NHS	D	10	DP7DN	20/32	10	30.4	8.25	43
12-16.5 NHS	D	8	DP7DJ	23/32	12.1	32.7	9.75	54
*12-16.5 NHS	D	8	DP8DJ	23/32	12.1	32.7	9.75	63
12-16.5 NHS	D	10	DP7DL	23/32	12.1	32.7	9.75	56

\* Steel Belted

### CHEVRON

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
7.00-15SS	B	6	DD1E1	20/32	7.8	29	5.5	28
*7.00-15SS	B	6	DD2E1	20/32	7.8	29	5.5	33



## DYNA TRAC® INDUSTRIAL RIB

These industrial handling tires are designed for use on smoother surfaces such as runways, airport baggage carriers.



**RIB DESIGN FOR INDUSTRIAL VEHICLES ON SMOOTH FLOORS AND RUNWAYS**

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
**4.80-8 NHS	A	4	DC3AX	6/32	4.8	16.1	3.75	7
4.80-8 NHS	A	6	DC3A1	6/32	4.8	16.1	3.75	6
5.70-8 NHS	A	6	DC3A3	7/32	5.8	18.2	4.5	9
5.70-8 NHS	A	8	DC3A4	7/32	5.8	18.2	4.5	9
5.70-8 NHS	A	12	DC3AY	7/32	5.8	18.2	4.5	14
6.90-9 NHS	A	4	DC3BL	11/32	6.9	21.4	5.5	12
6.90-9 NHS	A	6	DC3B1	11/32	6.9	21.4	5.5	14
6.90-9 NHS	A	8	DC3B2	11/32	6.9	21.4	5.5	15
6.90-9 NHS	A	10	DC3B3	11/32	6.9	21.4	5.5	17
6.50-10 NHS	A	4	DC5BN	12/32	7	23.5	5	15
6.50-10 NHS	A	6	DC5C1	12/32	7	23.5	5	18
**6.50-10 NHS	A	6	DC5NM	12/32	7	23.5	5	18
6.50-10 NHS	A	8	DC5C2	12/32	7	23.5	5	18
**6.50-10 NHS	A	8	DC5NP	12/32	7	23.5	5	19
6.50-10 NHS	A	10	DC5C3	12/32	7	23.5	5	20
9.00-10 NHS	B	10	DC3NB	10/32	9.4	27	6	30
9.00-10 NHS	B	12	DC3LA	10/32	9.4	27	6	36

\*\* Tubeless



## HEAVY DUTY RIB LUG

STA's heavy duty rib lug industrial handling tires are designed for work areas with smooth floors or runways. Providing better traction for your material handling applications.



FIG C



FIG D

HEAVY DUTY									
SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT	
*5.70-8 NHS	C	8	DC1A4	7/32	5.8	18.2	4.5	13	
*6.90-9 NHS	D	10	DC1B3	11/32	6.4	21.3	5.5	18	
*6.50-10 NHS	D	10	DC1C3	12/32	7.2	23.9	5	22	
*7.00-12 NHS	D	12	DC1D1	21/32	7.5	27.1	5	35	

## AMERICAN CARRIER

These extra heavy duty tires are designed for large container handlers, reach stackers and forklifts used in demanding environment of ports, rail terminals and container yards and offer excellent traction.



SIZE	PLY RATING	PRODUCT CODE	DESCRIP.	TREAD DEPTH	OVERALL DIA	RIM WIDTH	OVERALL WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
									5 MPH	
18.00-25	32	NE1LT	L4S	72/32	63.7	13	18	80	18810	872
18.00-25	40	NE1LW	L4S	72/32	63.7	13	18	80	37500	935



### BACK HOE FRONT TIRE: F3



FIG A



FIG B



FIG C



FIG D



FIG E

The Back Hoe Rib (F-3) tire is designed for steering axle service on tractors and backhoes in industrial service and features a 5 rib tread, deep saw tooth groove and wide footprint.

### INDUSTRIAL RIB F-3

SIZE	FIG	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAX INFLATION	MAX LOAD	WEIGHT
9.00-10SL	A	8	FA956	11/32	9.2	26.3	6	48	1570	22
9.00-10SL	A	10	FA958	11/32	9.2	26.3	6	60	1820	25
11L-15SL	D	10	FA9D7	16/32	11	31.8	8	52	2340	40
11L-15SL	D	14	FA9DB	16/32	11	31.8	8	68	2710	49
11L-16SL	E	10	FA4F7	16/32	11	33	8	52	2470	42
11L-16SL	E	14	FA4FB	16/32	11	33	8	72	2930	53
11.00-16SL	C	12	FA9T9	15/32	12.4	38.1	10	60	3420	53
14.5/75-16.1SL	B	10	FA46W	16/32	15.5	36.8	11	40	3200	65

### BACK HOW REAR TIRE: R4

Specialty Tire's R4 Premium tires for backhoes and industrial tractors.



FIG C



FIG D

### BACK HOE REAR TIRE R-4

SIZE	FIG	PLY	PRODUCT CODE	DESCRIP	TREAD DEPTH	OVERALL DIA	RIM WIDTH	OVERALL WIDTH	MAX INFLATION	MAX	WEIGHT
		Rating								LOAD 25 MPH	
14.9-24	C	8	NC5E3	R4	33/32	48.6	13	14.9	30	5080	119
16.9-24	C	8	NC5F3	R4	35/32	51.5	15	16.9	28	5840	148
17.5L-24	C	8	NC5H3	R4	33/32	49.2	15	17.5	26	5360	139
17.5L-24	C	12	NC5H5	R4	33/32	49.2	15	17.5	34	4680	151
18.4-24	C	10	NC5J5	R4	36/32	54.2	16	18.4	30	7400	176
19.5L-24	C	10	NC5K5	R4	34/32	51.5	17	19.5	28	6600	186
19.5L-24	C	12	NC5K7	R4	34/32	51.5	17	19.5	34	7600	191
21L-24	C	12	NC5L7	R4	35/32	54.5	18	21	32	8550	236
16.9-28	D	10	NC575	R4	31/32	56.5	15	18.1	32	6800	172
16.9-28	D	12	NC577	R4	31/32	56.5	15	18.1	38	7550	174



## LIGHT TRUCK BIAS PLY TIRES

### STA - Super Transport®

#### Tubeless Tires



#### Tube Type Tires



With its unique rib design for long mileage and cool running over highways, these tires are superior for light trucks including SUV's, 4x4's, vans, campers and motor homes. The STA Super Transport ® also features a wide profile that enhances traction and flotation.

SUPER TRANSPORT WB - TUBELESS											
SIZE	FIG	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAXIMUM LOAD AND INFLATION			
								DUAL LOAD	SINGLE LOAD	INFLATE	WGT
8.00-16.5LT	A	D/8	LA4A5	16/32	7.9	28.6	6	1800	2045	60	33
8.75-16.5LT	A	D/8	LA4B5	16/32	9	29.8	6.75	2070	2350	60	37
8.75-16.5LT	A	E/10	LA4B7	16/32	9	29.8	6.75	2360	2680	75	40
9.50-16.5LT	A	D/8	LA4C5	17/32	9.3	30.6	6.75	2445	2780	60	41
9.50-16.5LT	A	E/10	LA4C7	17/32	9.3	30.6	6.75	2790	3170	75	44
10-16.5LT	A	D/8	LA4D5	17/32	10.2	30.4	8.25	2420	2750	60	42
12-16.5LT	A	D/8	LA4E5	18/32	11.9	32.2	9.75	2640	3000	45	52
12-16.5LT	D	E/10	LC3E7	18/32	11.9	32.2	9.75	3120	3550	60	58
12-16.5LT	D	F/12	LC3EL	18/32	11.9	32.2	9.75	3560	4045	75	59
8-17.5LT	A	D/8	LA565	14/32	8	31.4	6	2155	2455	60	36
E78-14LT	A	D/8	LA3A5	15/32	7.7	26.5	5.5	1500	1710	60	28
G78-15LT	A	C/6	LA3B3	15/32	8.2	28.2	6	1460	1660	45	32
H78-15LT	A	C/6	LA3C3	16/32	8.6	29	6	1610	1830	45	34
L78-15LT	C	C/6	LF8H3	16/32	9.1	29.9	6.5	1790	2030	45	37
8.00-16.5LT	A	D/8	LA4A5	16/32	7.9	28.6	6	1800	2045	60	33
8.75-16.5LT	A	D/8	LA4B5	16/32	9	29.8	6.75	2070	2350	60	37
8.75-16.5LT	A	E/10	LA4B7	16/32	9	29.8	6.75	2360	2680	75	40
9.50-16.5LT	A	D/8	LA4C5	17/32	9.3	30.6	6.75	2445	2780	60	41
9.50-16.5LT	A	E/10	LA4C7	17/32	9.3	30.6	6.75	2790	3170	75	44
10-16.5LT	A	D/8	LA4D5	17/32	10.2	30.4	8.25	2420	2750	60	42
12-16.5LT	A	D/8	LA4E5	18/32	11.9	32.2	9.75	2640	3000	45	52
12-16.5LT	D	E/10	LC3E7	18/32	11.9	32.2	9.75	3120	3550	60	58
12-16.5LT	D	F/12	LC3EL	18/32	11.9	32.2	9.75	3560	4045	75	59



**STA - SUPER TRANSPORT (CONTINUED)**

<b>SUPER TRANSPORT LT - TUBELESS</b>											
SIZE	FIG	RANGE PLY	PRODUCT	TREAD	SECTION	OVERALL	RIM	MAXIMUM LOAD AND INFLATION			
		RATING	CODE	TREAD	WIDTH	DIA	WIDTH	D- LOAD	S- LOAD	INFLATE	WGT
9-14.5LT	B	G/14	LA5J6	12/32	7	28	9.5	3080	3505	115	42
6.70-15LT	E	C/6	LA113	15/32	7.4	28.5	5	1355	1530	45	27
7.00-15LT	A	C/6	LA223	15/32	7.9	29.6	5.5	1520	1720	45	32
7.00-15LT	A	D/8	LA225	15/32	7.9	29.6	5.5	1800	2040	60	32
6.50-16LT	E	C/6	LA133	12/32	7.4	29.9	4.5	1420	1610	45	28
7.50-16LT	A	D/8	LA245	15/32	8.7	32	6	2140	2440	60	37
7.50-16LT	A	E/10	LA247	15/32	8.7	32	6	2440	2780	75	45
<b>SUPER TRANSPORT LT - TUBE TYPE</b>											
SIZE	FIG	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAXIMUM LOAD AND INFLATION			
								DUAL LOAD	SINGLE LOAD	INFLATE	WGT
7.00-15LT	A	C/6	LA224	15/32	7.9	29.6	5.5	1520	1720	45	29
7.00-15LT	A	D/8	LA226	15/32	7.9	29.6	5.5	1800	2040	60	29
6.50-16LT	D	C/6	LA134	12/32	7.4	29.9	4.5	1420	1610	45	24
7.50-16LT	A	D/8	LA246	15/32	8.7	32	6	2140	2440	60	34
7.50-17LT	B	D/8	LA5J7	16/32	8.5	34.5	6	2460	2800	75	39
7.00-18LT	C	D/8	LA5J9	16/32	7.9	33.8	5.5	2270	2350	65	37
7.50-20	D	E/10	MA2A2	13/32	8.9	37.4	6	3100	3530	90	54



## STA SUPER TRAXION®

These long lasting and durable tires offer exceptional traction for pickups, vans, Campers on both highways and for off-road uses. These tires have a minimum stone retention design. Clean out is a snap as mud and stones are cast off as the tire rotates.

- \* Great traction with husky lugs
- \* Pinned for studs
- \* Cool running with deep vented shoulders
- \* Wide profile for flotation and traction



SUPER TRAXION WB TUBELESS											
SIZE	FIG	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAXIMUM LOAD AND INFLATION			
								DUAL LOAD	SINGLE LOAD	INFLATE	WT
8.00-16.5LT	A	D/8	LB4A5	17/32	8.1	28.9	6	1800	2045	60	31
8.75-16.5LT	A	D/8	LB4B5	18/32	8.8	29.9	6.75	2070	2350	60	38
8.75-16.5LT	A	E/10	LB4B7	18/32	8.8	29.9	6.75	2360	2680	75	38
9.50-16.5LT	A	D/8	LB4C5	18/32	9.5	31.1	6.75	2445	2780	60	40
10-16.5LT	A	D/8	LB4D5	20/32	10.2	30.7	8.25	2420	2750	60	44
12-16.5LT	A	D/8	LB4E5	21/32	11.9	32.8	9.75	2640	3000	45	53
12-16.5LT	A	E/10	LB4E7	21/32	11.9	32.8	9.75	3120	3550	60	57
8-17.5LT	B	D/8	LB565	14/32	8	31.4	6	2155	2455	60	45
SUPER TRAXION LT 78 TUBELESS											
SIZE	FIG	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAXIMUM LOAD AND INFLATION			
								DUAL LOAD	SINGLE LOAD	INFLATE	WT
E78-14LT	A	D/8	LB3A5	16/32	7.6	26.6	5.5	1500	1710	60	28
G78-15LT	A	C/6	LB3B3	17/32	8.2	28.5	6	4650	1660	45	32
H78-15LT	A	C/6	LB3C3	18/32	8.5	29.2	6	1610	1830	45	35
L78-15LT	A	D/8	LB3H5	18/32	9	30	6.5	2120	2400	65	37
SUPER TRAXION LT TUBELESS											
SIZE	FIG	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAXIMUM LOAD AND INFLATION			
								DUAL LOAD	SINGLE LOAD	INFLATE	WT
7.00-15LT	A	C/6	LB223	18/32	7.9	30	5.5	1520	1720	45	30
7.50-16LT	A	D/8	LB245	18/32	8.7	32.2	6	2140	2440	60	37
SUPER TRAXION LT TUBE TYPE											
SIZE	FIG	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIA	RIM WIDTH	MAXIMUM LOAD AND INFLATION			
								DUAL LOAD	SINGLE LOAD	INFLATE	WT
7.00-15LT	A	C/6	LB224	18/32	7.9	29.6	5.5	1520	1720	45	30
7.00-15LT	A	D/8	LB226	18/32	7.9	30	5.5	1800	2040	60	31
6.50-16LT	C	C/6	LB134	19/32	7.2	30.2	4.5	1420	1610	45	32
7.50-16LT	A	D/8	LB246	18/32	8.7	32.2	6	2140	2440	60	37



Specialty Tires of America produced tires are designed to be used with rims having the dimensions of those shown as "approved rims" for the tire size in the Tire and Rim Association Yearbook. Current at the time of tire manufacture. Use of other rims must be specifically approved by Specialty Tires of America.



## STA TRAILBREAKER®

Boldly go where no one else can with the STA Trailbreaker®, specifically built to perform on SUV's, 4x4's, vans and pickups. Featuring an aggressive tread for on and off road use that lasts longer, these tires go the distance for you.

- \* Deep cleats for greater traction in rough off road use.
- \* Raised white outline letters.
- \* Heavy sipes for extra traction and cooling.
- \* Tubeless



**STA TRAILBREAKER**

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIA	MAXIMUM INFLATION	MAX LOAD	WEIGHT
L78-15LT	C/6	LF3HC	17/32	6.5	9.1	29.9	45	2030	37
10-15LT	C/6	LF2HC	21/32	8	10.6	30.4	45	2230	41
11-15LT	C/6	LF2JC	21/32	8	11.4	30.7	45	2410	45
12-15LT	C/6	LF2KC	21/32	10	13	32.1	30	2250	52
35X14.5-15LT	C/6	LF2PC	23/32	11.5	13.7	34.8	30	2725	60
35X14.5-16.5LT	C/6	LF2TC	23/32	11.25	13.2	34.8	30	2845	62
12-16.5LT	D/8	LF2EE	21/32	9.75	12.7	32.6	45	3000	55

## STA SUPERLUG®

Rise above the rest with the STA Superlug®, with its higher ground clearance/overall diameter and incredible traction for SUV's, 4x4's and pickups both on and off the roads. This heavy-duty tire offers a stability to go with secure "footing" than found with radial tires in similar applications. These tires are preferred by the military for severe off road needs.



**SUPERLUG - Tubeless - Nylon Construction - Raised White Outline Letters**

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIA	MAX INFLATION PSI	MAX LOAD	WEIGHT
9.00-16LT	D/8	LT28E	21/32	6.5	10.38	36.3	50	2665(D) 3030(S)	58

(D) = DUAL

(S) = SINGLE

**SUPERLUG - Tube Type - Nylon Construction - Black Wall**

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIA	MAX INFLATION PSI	MAX LOAD	WEIGHT
9.00-16LT	D/8	LT286	21/32	6.5	10.38	36.3	50	2665(D) 3030(S)	58

(D) = DUAL

(S) = SINGLE



## STA NON-DIRECTIONAL MILITARY TIRES

High-quality tires for your refurbished jeeps and older military vehicles as well as general purpose tires for cranes, shovels and dump trucks. The non-directional tread design on these high-quality tires provides equal traction in either direction.



### NDT SERIES

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAX INFLATION	MAX LOAD	WEIGHT
7.50-10NHS	B/4	DN1L2	9/32	6	8.3	24.8	40	2260	21
6.00-16	B/4	LN1W2	16/32	4.5	6.7	28.6	30	1130	21
6.00-16	C/6	LN1W4	16/32	4.5	6.7	28.6	45	1430	22
7.00-16	C/6	LN174	17/32	5.5	7.6	31.8	45	1800	29
7.50-16	D/8	LN146	17/32	6	8.5	32.5	60	2440	32
7.50-16	E/10	LN148	17/32	6	8.5	32.5	75	2780	37
9.00-16	D/8	LN18E	18/32	7	10.2	35.5	50	2665	48
7.50-20	D/8	ML4AB	17/32	6	9	38.5	60	3330	49
8.25-20	F/12	ML4B4	19/32	6.5	9.5	39.5	100	2060	60
9.00-20	F/12	ML4C4	20/32	7	10.6	40.7	95	5150	72
11.00-20	G/14	ML4E6	20/32	8	11.9	43	100	6590	110
12.00-20	G/14	HL4F6	20/32	8.5	12.5	44.8	90	7000	113
12.00-20	H/16	HL4F8	20/32	8.5	12.5	44.8	105	7740	114
12.00-20	J/18	HL4FA	20/32	8.5	12.5	44.8	115	8210	128

### NDCC SERIES

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAX INFLATION	MAX LOAD	WEIGHT
7.00-15	C/6	LN124	16/32	5.5	7.8	29.5	45	1720	25
7.00-16	C/6	LN27C	17/32	5.5	7.6	31.1	45	1800	29
9.00-20	D/8	ML5CB	19/32	7	9.8	41.2	65	4000	63
11.00-20	F/12	ML5E4	22/32	8	10	43.5	85	5920	93
14.00-20	G/14	HL5M6	24/32	10	15	49.5	50	6410	121
14.00-20	L/20	HL5MC	24/32	10	15	49.5	95	9960	173
14.00-20NHS	G/14	DN2LY	24/32	10	15.2	49.5	54	11435	113
14.00-20NHS	L/20	DN2LX	24/32	10	15.2	49.5	102	16500	146
7.00-15	C/6	LN124	16/32	5.5	7.8	29.5	45	1720	25



## SUPER TRANSPORT / SUPER TRAXION ®



High quality and durability tires perfect for older United States Postal Service (USPS) equipment and vehicles.

SUPER TRANSPORT / SUPER TRAXION									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIA	MAX INFLATION	MAX LOAD	WEIGHT
<b>SUPER TRANSPORT</b>									
P185/75D14	B	PA1H2	11/32	5	6.8	25.5	32	1235	17
P205/75D15	B	PA1Y6	11/32	5.5	7.7	27.1	32	1532	22
<b>SUPER TRAXION</b>									
P185/75D14	B	PA2H2	11/32	5	6.8	25.5	32	1235	18
P205/75D15	B	PA2Y6	11/32	5.5	7.7	27.2	32	1532	25

## NDCC Non-Directional Military Tires

High-quality tires for Post World War II vehicles. The non-directional tread design on these high-quality tires provides equal traction in either direction.



NDCC SERIES									
SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAX INFLATION	MAX LOAD	WEIGHT
7.00-15	C/6	LN124	16/32	5.5	7.8	29.5	45	1720	25
7.00-16	C/6	LN27C	17/32	5.5	7.6	31.1	45	1800	29
9.00-20	D/8	ML5CB	19/32	7	9.8	41.2	65	4000	63
11.00-20	F/12	ML5E4	22/32	8	10	43.5	85	5920	93
14.00-20	G/14	HL5M6	24/32	10	15	49.5	50	6410	121
14.00-20	L/20	HL5MC	24/32	10	15	49.5	95	9960	173
14.00-20NHS	G/14	DN2LY	24/32	10	15.2	49.5	54	11435	113
14.00-20NHS	L/20	DN2LX	24/32	10	15.2	49.5	102	16500	146
7.00-15	C/6	LN124	16/32	5.5	7.8	29.5	45	1720	25